

Package ‘PBSmodelling’

February 21, 2012

Version 2.63.229

Date 2011-09-09

Title GUI Tools Made Easy: Interact with Models, Explore Data, Give Dynamic Presentations

Author Jon T. Schnute <Jon.Schnute@dfo-mpo.gc.ca>, Alex Couture-Beil <aLex@mofo.ca>, Rowan Haigh <rowan.haigh@dfo-mpo.gc.ca>, and A.R. (Rob) Kronlund <Allen.Kronlund@dfo-mpo.gc.ca>

Maintainer Jon Schnute <Jon.Schnute@dfo-mpo.gc.ca>

Depends R (>= 2.7.0), methods

Suggests PBSmapping, PBSddesolve, deSolve, KernSmooth, XML

Description PBS Modelling provides software to facilitate the design, testing, and operation of computer models. It focuses particularly on tools that make it easy to construct and edit a customized graphical user interface (GUI). Although it depends heavily on the R interface to the Tcl/Tk package, a user does not need to know Tcl/Tk. The package contains examples that illustrate models built with other R packages, including PBSmapping, deSolve, PBSddesolve, and BRugs. It also serves as a convenient prototype for building new R packages, along with instructions and batch files to facilitate that process. The R directory ‘.../library/PBSmodelling/doc’ includes a complete user guide PBSmodelling-UG.pdf. To use this package effectively, please consult the guide.

License GPL (>= 2)

Repository CRAN

Date/Publication 2011-09-10 06:17:24

R topics documented:

addArrows	4
addLabel	5
addLegend	6

calcFib	6
calcGM	7
calcMin	8
CCA.qbr	10
chooseWinVal	11
cleanProj	13
cleanWD	14
clearAll	15
clearPBSext	15
clearRcon	16
clearWinVal	17
clipVector	17
closeWin	18
compileC	19
compileDescription	20
convSlashes	20
createVector	21
createWin	22
declareGUIoptions	24
doAction	25
drawBars	26
evalCall	26
expandGraph	27
exportHistory	28
findPat	29
findPrefix	29
findProgram	30
focusWin	31
genMatrix	32
getChoice	33
getGUIoptions	34
getOptions	35
getOptionsFileName	35
getOptionsPrefix	36
getPBSext	37
getPBSoptions	38
getWinAct	38
getWinFun	39
getWinVal	39
getYes	40
GT0	41
importHistory	42
initHistory	43
isWhat	45
loadC	46
loadOptions	47
loadOptionsGUI	48
openExamples	48

openFile	49
openPackageFile	51
openProjFiles	52
openUG	53
packList	54
pad0	55
parseWinFile	56
pause	57
PBSmodelling	57
PBSoptions-class	58
pickCol	59
plotACF	60
plotAsp	61
plotBubbles	62
plotCsum	63
plotDens	64
plotFriedEggs	65
plotTrace	66
presentTalk	67
promptOpenFile	68
promptSaveFile	69
promptWriteOptions	70
readList	71
readPBSoptions	71
resetGraph	72
restorePar	73
runDemos	74
runExample	74
runExamples	75
scalePar	76
selectDir	77
selectFile	78
setFileOption	79
setGUIoptions	80
setPathOption	81
setPBSext	82
setPBSoptions	82
setwdGUI	83
setWidgetColor	83
setWidgetState	85
setWinAct	86
setWinVal	87
show0	88
showAlert	89
showArgs	90
showHelp	90
showPacks	91
showRes	92

showVignettes	93
sortHistory	93
talk-class	94
testAlpha	96
testCol	97
testLty	98
testLwd	99
testPch	99
testWidgets	100
unpackList	103
updateGUI	104
vbdata	105
vbpars	105
view	106
viewCode	107
writeList	108
writePBSoptions	109

Index **110**

addArrows *Add Arrows to a Plot Using Relative (0:1) Coordinates*

Description

Call the arrows function using relative (0:1) coordinates.

Usage

```
addArrows(x1, y1, x2, y2, ...)
```

Arguments

x1	x-coordinate (0:1) at base of arrow.
y1	y-coordinate (0:1) at base of arrow.
x2	x-coordinate (0:1) at tip of arrow.
y2	y-coordinate (0:1) at tip of arrow.
...	additional paramaters for the function arrows.

Details

Lines will be drawn from $(x1[i], y1[i])$ to $(x2[i], y2[i])$

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

See Also

[addLabel](#), [addLegend](#)

Examples

```
tt=seq(from=-5,to=5,by=0.01)
plot(sin(tt), cos(tt)*(1-sin(tt)), type="l")
addArrows(0.2,0.5,0.8,0.5)
addArrows(0.8,0.95,0.95,0.55, col="#FF0066")
```

addLabel

Add a Label to a Plot Using Relative (0:1) Coordinates

Description

Place a label in a plot using relative (0:1) coordinates

Usage

```
addLabel(x, y, txt, ...)
```

Arguments

x	x-axis coordinate in the range (0:1); can step outside.
y	y-axis coordinate in the range (0:1); can step outside.
txt	desired label at (x,y).
...	additional arguments passed to the function text.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

See Also

[addArrows](#), [addLegend](#)

Examples

```
resetGraph()
addLabel(0.75,seq(from=0.9,to=0.1,by=-0.10),c('a','b','c'), col="#0033AA")
```

`addLegend`*Add a Legend to a Plot Using Relative (0:1) Coordinates*

Description

Place a legend in a plot using relative (0:1) coordinates.

Usage

```
addLegend(x, y, ...)
```

Arguments

<code>x</code>	x-axis coordinate in the range (0:1); can step outside.
<code>y</code>	y-axis coordinate in the range (0:1); can step outside.
<code>...</code>	arguments used by the function <code>legend</code> , such as <code>lines</code> , <code>text</code> , or <code>rectangle</code> .

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

See Also

[addArrows](#), [addLabel](#)

Examples

```
resetGraph(); n <- sample(1:length(colors()),15); clr <- colors()[n]
addLegend(.2,1,fill=clr,leg=clr,cex=1.5)
```

`calcFib`*Calculate Fibonacci Numbers by Several Methods*

Description

Compute Fibonacci numbers using four different methods: 1) iteratively using R code, 2) via the closed function in R code, 3) iteratively in C using the `.C` function, and 4) iteratively in C using the `.Call` function.

Usage

```
calcFib(n, len=1, method="C")
```

Arguments

n	nth fibonacci number to calculate
len	a vector of length len showing previous fibonacci numbers
method	select method to use: C, Call, R, closed

Value

Vector of the last len Fibonacci numbers calculated.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

calcGM

Calculate the Geometric Mean, Allowing for Zeroes

Description

Calculate the geometric mean of a numeric vector, possibly excluding zeroes and/or adding an offset to compensate for zero values.

Usage

```
calcGM(x, offset = 0, exzero = TRUE)
```

Arguments

x	vector of numbers
offset	value to add to all components, including zeroes
exzero	if TRUE, exclude zeroes (but still add the offset)

Value

Geometric mean of the modified vector $x + \text{offset}$

Note

NA values are automatically removed from x

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

Examples

```
calcGM(c(0,1,100))  
calcGM(c(0,1,100),offset=0.01,exzero=FALSE)
```

 calcMin

Calculate the Minimum of a User-Defined Function

Description

Minimization based on the R-stat functions `nlm`, `nlminb`, and `optim`. Model parameters are scaled and can be active or not in the minimization.

Usage

```
calcMin(pvec, func, method="nlm", trace=0, maxit=1000, reltol=1e-8,
        steptol=1e-6, temp=10, repN=0, ...)
```

Arguments

<code>pvec</code>	Initial values of the model parameters to be optimized. <code>pvec</code> is a data frame comprising four columns (<code>"val"</code> , <code>"min"</code> , <code>"max"</code> , <code>"active"</code>) and as many rows as there are model parameters. The <code>"active"</code> field (logical) determines whether the parameters are estimated (T) or remain fixed (F).
<code>func</code>	The user-defined function to be minimized (or maximized). The function should return a scalar result.
<code>method</code>	The minimization method to use: one of <code>nlm</code> , <code>nlminb</code> , Nelder-Mead, BFGS, CG, L-BFGS-B, or SANN. Default is <code>nlm</code> .
<code>trace</code>	Non-negative integer. If positive, tracing information on the progress of the minimization is produced. Higher values may produce more tracing information: for method <code>"L-BFGS-B"</code> there are six levels of tracing. Default is 0.
<code>maxit</code>	The maximum number of iterations. Default is 1000.
<code>reltol</code>	Relative convergence tolerance. The algorithm stops if it is unable to reduce the value by a factor of <code>reltol*(abs(val)+reltol)</code> at a step. Default is <code>1e-8</code> .
<code>steptol</code>	A positive scalar providing the minimum allowable relative step length. Default is <code>1e-6</code> .
<code>temp</code>	Temperature controlling the <code>"SANN"</code> method. It is the starting temperature for the cooling schedule. Default is 10.
<code>repN</code>	Reports the parameter and objective function values on the R-console every <code>repN</code> evaluations. Default is 0 for no reporting.
<code>...</code>	Further arguments to be passed to the optimizing function chosen: <code>nlm</code> , <code>nlminb</code> , or <code>optim</code> . Beware of partial matching to earlier arguments.

Details

See `optim` for details on the following methods: Nelder-Mead, BFGS, CG, L-BFGS-B, and SANN.

Value

A list with components:

<code>Fout</code>	The output list from the optimizer function chosen through <code>method</code> .
<code>iters</code>	Number of iterations.
<code>evals</code>	Number of evaluations.
<code>cpuTime</code>	The user CPU time to execute the minimization.
<code>elapsedTime</code>	The total elapsed time to execute the minimization.
<code>fminS</code>	The objective function value calculated at the start of the minimization.
<code>fminE</code>	The objective function value calculated at the end of the minimization.
<code>Pstart</code>	Starting values for the model parameters.
<code>Pend</code>	Final values estimated for the model parameters from the minimization.
<code>AIC</code>	Akaike's Information Criterion
<code>message</code>	Convergence message from the minimization routine.

Note

Some arguments to `calcMin` have no effect depending on the method chosen.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

See Also

[scalePar](#), [restorePar](#), [calcMin](#), [GT0](#)

In the stats package: `nlm`, `nlminb`, and `optim`.

Examples

```
Ufun <- function(P) {
  Linf <- P[1]; K <- P[2]; t0 <- P[3]; obs <- afile$len;
  pred <- Linf * (1 - exp(-K*(afile$age-t0)));
  n <- length(obs); ssq <- sum((obs-pred)^2 );
  return(n*log(ssq)); };
afile <- data.frame(age=1:16,len=c(7.36,14.3,21.8,27.6,31.5,35.3,39,
41.1,43.8,45.1,47.4,48.9,50.1,51.7,51.7,54.1));
pvec <- data.frame(val=c(70,0.5,0),min=c(40,0.01,-2),max=c(100,2,2),
  active=c(TRUE,TRUE,TRUE),row.names=c("Linf","K","t0"),
  stringsAsFactors=FALSE);
alist <- calcMin(pvec=pvec,func=Ufun,method="nlm",steptol=1e-4,repN=10);
print(alist[-1]); P <- alist$Pend;
resetGraph(); expandGraph();
xnew <- seq(afile$age[1],afile$age[nrow(afile)],len=100);
ynew <- P[1] * (1 - exp(-P[2]*(xnew-P[3])) );
plot(afile); lines(xnew,ynew,col="red",lwd=2);
addLabel(.05,.88,paste(paste(c("Linf","K","t0")),round(P,c(2,4,4)),
  sep=" = "),collapse="\n"),adj=0,cex=0.9);
```

CCA.qbr

*Data: Sampled Counts of Quillback Rockfish (Sebastes maliger)***Description**

Count of sampled fish-at-age for quillback rockfish (*Sebastes maliger*) in Johnstone Strait, British Columbia, from 1984 to 2004.

Usage

```
data(CCA.qbr)
```

Format

A matrix with 70 rows (ages) and 14 columns (years). Attributes “syrs” and “cyrs” specify years of survey and commercial data, respectively.

```
[, c(3:5, 9, 13, 14)]    Counts-at-age from research survey samples
[, c(1, 2, 6:8, 10:12)]  Counts-at-age from commercial fishery samples
```

All elements represent sampled counts-at-age in year. Zero-value entries indicate no observations.

Details

Handline surveys for rockfish have been conducted in Johnstone Strait (British Columbia) and adjacent waterways (126°37'W to 126°53'W, 50°32'N to 50°39'N) since 1986. Yamanaka and Richards (1993) describe surveys conducted in 1986, 1987, 1988, and 1992. In 2001, the Rockfish Selective Fishery Study (Berry 2001) targeted quillback rockfish *Sebastes maliger* for experiments on improving survival after capture by hook and line gear. The resulting data subsequently have been incorporated into the survey data series. The most recent survey in 2004 essentially repeated the 1992 survey design. Fish samples from surveys have been supplemented by commercial hand-line fishery samples taken from a larger region (126°35'W to 127°39'W, 50°32'N to 50°59'N) in the years 1984-1985, 1989-1991, 1993, 1996, and 2000 (Schnute and Haigh 2007).

Note

Years 1994, 1997-1999, and 2002-2003 do not have data.

Source

Fisheries and Oceans Canada - GFBio database:
http://www-sci.pac.dfo-mpo.gc.ca/sa-mfpd/statsamp/StatSamp_GFBio.htm

References

Berry, M.D. (2001) *Area 12 (Inside) Rockfish Selective Fishery Study*. Science Council of British Columbia, Project Number **FS00-05**.

Schnute, J.T. and Haigh, R. (2007) Compositional analysis of catch curve data with an application to *Sebastes maliger*. *ICES Journal of Marine Science* **64**, 218–233.

Yamanaka, K.L. and Richards, L.J. (1993) 1992 Research catch and effort data on nearshore reef-fishes in British Columbia Statistical Area 12. *Canadian Manuscript Report of Fisheries and Aquatic Sciences* **2184**, 77 pp.

Examples

```
# Plot age proportions (blue bubbles = survey data, red = commercial)
data(CCA.qbr); clr=c("cornflowerblue","orangered")
z <- CCA.qbr; cyr <- attributes(z)$cyr;
z <- apply(z,2,function(x){x/sum(x)}); z[,cyr] <- -z[,cyr];
x <- as.numeric(dimnames(z)[[2]]); xlim <- range(x) + c(-.5,.5);
y <- as.numeric(dimnames(z)[[1]]); ylim <- range(y) + c(-1,1);
expandGraph(mgp=c(2,.5,0),las=1)
plotBubbles(z,xval=x,yval=y,pow=.5,size=0.15,clr=clr,
  xlim=xlim,ylim=ylim,xlab="Year",ylab="Age",cex.lab=1.5)
addLegend(.5,1,bty="n",pch=1,cex=1.2,col=clr,
  legend=c("Survey","Commercial"),horiz=TRUE,xjust=.5)
```

chooseWinVal

Choose and Set a String Item in a GUI

Description

Prompts the user to choose one string item from a list of choices displayed in a GUI, then sets a specified variable in a target GUI.

Usage

```
chooseWinVal(choice, varname, winname="window")
```

Arguments

choice	vector of strings from which to choose
varname	variable name to which choice is assigned in the target GUI
winname	window name for the target GUI

Details

chooseWinVal activates a setWinVal command through an onClose function created by the getChoice command and modified by chooseWinVal.

Value

No value is returned directly. The choice is written to the PBS options workspace, accessible through `getPBSoptions("getChoice")`. Also set in PBS options is the window name from which the choice was activated.

Note

Microsoft Windows users may experience difficulties switching focus between the R console and GUI windows. The latter frequently disappear from the screen and need to be reselected (either clicking on the task bar or pressing <Alt><Tab>. This issue can be resolved by switching from MDI to SDI mode. From the R console menu bar, select <Edit> and <GUI preferences>, then change the value of “single or multiple windows” to SDI.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

See Also

[getChoice](#), [getWinVal](#), [setWinVal](#)

Examples

```
## Not run:
dfnam <-
c("airquality","attitude","ChickWeight","faithful","freeny",
  "iris","LifeCycleSavings","longley","morley","Orange",
  "quakes","randu","rock","stackloss","swiss","trees")

wlist <- c(
  "window name=choisir title=\"Test chooseWinVal\"",
  "label text=\"Press <ENTER> in the green entry box
  \nto choose a file, then press <GO>\" sticky=W pady=5",
  "grid 1 3 sticky=W",
  "label text=File: sticky=W",
  "entry name=fnam mode=character width=23 value=\"\"",
  func=chFile entrybg=darkolivegreen1 pady=5",
  "button text=GO bg=green sticky=W func=test",
  "")

chFile <- function(ch=dfnam,fn="fnam")
{chooseWinVal(ch,fn,winname="choisir")};

#-- Example 1 GUI test
test <- function() {
  getWinVal(winName="choisir",scope="L")
  if (fnam!=" " && any(fnam==dfnam)) {
    file <- get(fnam);
    pairs(file,gap=0); }
  else {
    resetGraph();
    addLabel(.5,.5,"Press <ENTER> in the green entry box
    \nto choose a file, then press <GO>", col="red",cex=1.5)};

#-- Example 2 Non-GUI test
#To try the non-GUI version, type 'test2()' on the command line
test2 <- function(fnames=dfnam) {
```

```

frame();resetGraph()
again <- TRUE;
while (again) {
  fnam <- sample(fnames,1); file <- get(fnam);
  flds <- names(file);
  xfld <- getChoice(paste("Pick x-field from",fnam),flds,gui=F);
  yfld <- getChoice(paste("Pick y-field from",fnam),flds,gui=F)
  plot(file[,xfld],file[,yfld],xlab=xfld,ylab=yfld,
       pch=16,cex=1.2,col="red");
  again <- getChoice("Plot another pair?",gui=F) }
}
require(PBSmodelling)
createWin(wlist,astext=T); test();

## End(Not run)

```

cleanProj

Launch a GUI for Project File Deletion

Description

Launches a new window which contains an interface for deleting junk files associated with a prefix and a set of suffixes (e.g., PBSadmb project) from the working directory.

Usage

```
cleanProj(prefix, suffix, files)
```

Arguments

prefix	default prefix for file names.
suffix	character vector of suffixes used for clean options.
files	character vector of file names used for clean options.

Details

All arguments may contain wildcard characters ("*" to match 0 or more characters, "?" to match any single character).

The GUI includes the following:

- 1 An entry box for the prefix.
The default value of this entry box is taken from `prefix`.
- 2 Check boxes for each suffix in the `suffix` argument and for each file name in the `files` argument.
- 3 Buttons marked "Select All" and "Select None" for selecting and clearing all the check boxes, respectively.
- 4 A "Clean" button that deletes files in the working directory matching one of the following criteria:

- (i) file name matches both an expansion of a concatenation of a prefix in the entry box and a suffix chosen with a check box; or
- (ii) file name matches an expansion of a file chosen with a check box.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

Examples

```
## Not run:
cleanProj(prefix="foo",suffix=c(".a*",".b?",".c","-old.d"),files=c("red","blue"))

## End(Not run)
```

cleanWD

Launch a GUI for File Deletion

Description

Launches a new window which contains an interface for deleting specified files from the working directory.

Usage

```
cleanWD(files)
```

Arguments

files character vector of file names used for clean options.

Details

All arguments may contain wildcard characters ("*" to match 0 or more characters, "?" to match any single character).

The GUI includes the following:

- 1 Check boxes for each suffix in the `suffix` argument and for each file name in the `files` argument.
- 2 Buttons marked "Select All" and "Select None" for selecting and clearing all the check boxes, respectively.
- 3 A "Clean" button that deletes files in the working directory matching file name expansion of files chosen with a check box.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

Examples

```
## Not run:
cleanWD(c("*.*bak", "*.*tmp", "junk*"))

## End(Not run)
```

clearAll	<i>Remove all R Objects From the Global Environment</i>
----------	---

Description

Generic function to clear all objects from .RData in R

Usage

```
clearAll(hidden=TRUE, verbose=TRUE, PBSSave=TRUE)
```

Arguments

hidden	if TRUE, remove variables that start with a dot(.).
verbose	if TRUE, report all removed items.
PBSSave	if TRUE, do not remove .PBSmod.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

clearPBSext	<i>Clear File Extension Associations</i>
-------------	--

Description

Disassociate any number of file extensions from commands previously saved with setPBSext.

Usage

```
clearPBSext(ext)
```

Arguments

ext	optional character vector of file extensions to clear; if unspecified, all associations are removed
-----	---

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[setPBSext](#), [getPBSext](#), [openFile](#)

clearRcon

Clear the R Console Window

Description

Clear the R console window using a Visual Basic shell script.

Usage

```
clearRcon(os=.Platform$OS.type)
```

Arguments

os operating system (e.g., "windows", "unix").

Details

Creates a VB shell script file called `clearRcon.vba` in R's temporary working directory, then executes the script using the shell command.

Similarly, `focusRcon()` gives the focus to the R console window by creating a Visual Basic shell script called `focusRgui.vba` in R's temporary working directory, then executes it using the shell command.

These commands will only work on Windows operating platforms, using the system's executable `%SystemRoot%\system32\cscript.exe`.

Author(s)

Norm Olsen, Pacific Biological Station, Nanaimo BC

See Also

[cleanWD](#), [clearPBSext](#), [clearWinVal](#)

clearWinVal	<i>Remove all Current Widget Variables</i>
-------------	--

Description

Remove all global variables that share a name in common with any widget variable name defined in `names(getWinVal())`. Use this function with caution.

Usage

```
clearWinVal()
```

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[getWinVal](#)

clipVector	<i>Clip a Vector at One or Both Ends</i>
------------	--

Description

Clip a vector at one or both ends using the specified clip pattern to match.

Usage

```
clipVector(vec, clip, end=0)
```

Arguments

vec	vector object to clip
clip	value or string specifying repeated values to clip from ends
end	end to clip clip from: 0=both, 1=front, 2=back

Details

If the vector is named, the names are retained. Otherwise, element positions are assigned as the vector's names.

Value

Clipped vector with names.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

See Also

[createVector](#)

Examples

```
x=c(0,0,0,0,1,1,1,1,0,0)
clipVector(x,0)
```

```
x=c(TRUE,TRUE,FALSE,TRUE)
clipVector(x,TRUE)
```

```
x=c("red","tide","red","red")
clipVector(x,"red",2)
```

closeWin

Close GUI Window(s)

Description

Close (destroy) one or more windows made with createWin.

Usage

```
closeWin(name)
```

Arguments

name	a vector of window names that indicate which windows to close. These names appear in the <i>window description file(s)</i> on the line(s) defining WINDOW widgets. If name is omitted, all active windows will be closed.
------	---

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[createWin](#)

`compileC`*Compile a C File into a Shared Library Object*

Description

This function provides an alternative to using R's SHLIB command to compile C code into a shared library object.

Usage

```
compileC(file, lib="", options="", logWindow=TRUE, logFile=TRUE)
```

Arguments

<code>file</code>	name of the file to compile.
<code>lib</code>	name of shared library object (without extension).
<code>options</code>	linker options (in one string) to prepend to a compilation command.
<code>logWindow</code>	if TRUE, a log window containing the compiler output will be displayed.
<code>logFile</code>	if TRUE, a log file containing the compiler output will be created.

Details

If `lib=""`, it will take the same name as `file` (with a different extension).

If an object with the same name has already been dynamically loaded in R, it will be unloaded automatically for recompilation.

The name of the log file, if created, uses the string value from `lib` concatenated with `".log"`.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[loadC](#)

Examples

```
## Not run:  
compileC("myFile.c", lib="myLib", options="myObj.o")  
  
## End(Not run)
```

compileDescription *Convert and Save a Window Description as a List*

Description

Convert a *window description file* (ASCII markup file) to an equivalent *window description list*. The output list (an ASCII file containing R-source code) is complete, i.e., all default values have been added.

Usage

```
compileDescription(descFile, outFile)
```

Arguments

descFile name of *window description file* (markup file).
outFile name of output file containing R source code.

Details

The *window description file* descFile is converted to a list, which is then converted to R code, and saved to outFile.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[parseWinFile](#), [createWin](#)

convSlashes *Convert Slashes from UNIX to DOS*

Description

Convert slashes in a string from '/' to '\\\' if the operating system is 'windows'. Do the reverse if the OS is 'unix'.

Usage

```
convSlashes(expr, os=.Platform$OS.type, addQuotes=FALSE)
```

Arguments

expr	String value (usually a system pathway).
os	operating system (either "windows" or "unix").
addQuotes	logical: if TRUE, enclose the string expression in escaped double quotation marks.

Value

Returns the input string modified to have the appropriate slashes for the specified operating system.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

createVector *Create a GUI with a Vector Widget*

Description

Create a basic window containing a vector and a submit button. This provides a quick way to create a window without the need for a *window description file*.

Usage

```
createVector(vec, vectorLabels=NULL, func="",  
            windowname="vectorwindow")
```

Arguments

vec	a vector of strings representing widget variables. The values in vec become the default values for the widget. If vec is named, the names are used as the variable names.
vectorLabels	an optional vector of strings to use as labels above each widget.
func	string name of function to call when new data are entered in widget boxes or when "GO" is pressed.
windowname	unique window name, required if multiple vector windows are created.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[createWin](#)

Examples

```
## Not run:
#user defined function which is called on new data
drawLiss <- function() {
  getWinVal(scope="L");
  tt <- 2*pi*(0:k)/k; x <- sin(2*pi*m*tt); y <- sin(2*pi*(n*tt+phi));
  plot(x,y,type="p"); invisible(NULL); };

#create the vector window
createVector(c(m=2, n=3, phi=0, k=1000),
  vectorLabels=c("x cycles", "y cycles", "y phase", "points"),
  func="drawLiss");

## End(Not run)
```

createWin

Create a GUI Window

Description

Create a GUI window with widgets using instructions from a Window Description (markup) File.

Usage

```
createWin( fname, astext=FALSE, env=parent.frame() )
```

Arguments

fname	name of <i>window description file</i> or list returned from parseWinFile.
astext	logical: if TRUE, interpret fname as a vector of strings with each element representing a line in a <i>window description file</i> .
env	an environment in which to evaluate widget callback functions; see example.

Details

Generally, the markup file contains a single widget per line. However, widgets can span multiple lines by including a backslash (`\`) character at the end of a line, prompting the suppression of the newline character.

For more details on widget types and markup file, see “PBSModelling-UG.pdf” in the R directory `.../library/PBSmodelling/doc`.

It is possible to use a Window Description List produced by `compileDescription` rather than a file name for `fname`.

Another alternative is to pass a vector of characters to `fname` and set `astext=T`. This vector represents the file contents where each element is equivalent to a new line in the *window description file*.

Note

Microsoft Windows users may experience difficulties switching focus between the R console and GUI windows. The latter frequently disappear from the screen and need to be reselected (either clicking on the task bar or pressing <Alt><Tab>. This issue can be resolved by switching from MDI to SDI mode. From the R console menu bar, select <Edit> and <GUI preferences>, then change the value of “single or multiple windows” to SDI.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[parseWinFile](#), [getWinVal](#), [setWinVal](#)
[closeWin](#), [compileDescription](#), [createVector](#)
[initHistory](#) for an example of using `astext=TRUE`
[environment](#)

Examples

```
## Not run:
# See file ../library/PBSmodelling/testWidgets/LissWin.txt

# Calculate and draw the Lissajous figure
drawLiss <- function() {
  getWinVal(scope="L"); ti=2*pi*(0:k)/k;
  x=sin(2*pi*m*ti); y=sin(2*pi*(n*ti+phi));
  plot(x,y,type=pptype); invisible(NULL); };
createWin(system.file("testWidgets/LissWin.txt",package="PBSmodelling"));

## End(Not run)

#####
# Environment example:

#function in global
hello <- function()
{
  stop( "I shouldn't be called" )
}

newNameGreeter <- function( name )
{
  #method to display window
  greet <- function()
  {
    createWin( c( "button \"say hello\" func=hello" ), astext=TRUE, env = parent.env( environment() ) )
  }
}
```

```
#hello method will refer to the name in this local scope
hello <- function()
{
  cat( "Hello", name, "\n" )
}

#return functions which the user can call directly
return( list( greet = greet, hello = hello ) )
}

alex <- newNameGreeter( "Alex" )
jon <- newNameGreeter( "Jon" )

alex$hello() #prints hello Alex
jon$hello() #hello Jon

alex$greet() #creates a GUI with a button, which will print "hello Alex" when pushed
```

declareGUIoptions *Declare Option Names that Correspond with Widget Names*

Description

This function allows a GUI creator to specify widget names that correspond to names in PBS options. These widgets can then be used to load and set PBS options using `getGUIoptions` and `setGUIoptions`.

Usage

```
declareGUIoptions(newOptions)
```

Arguments

`newOptions` a character vector of option names

Details

`declareGUIoptions` is typically called in a GUI initialization function. The option names are remembered and used for the functions `getGUIoptions`, `setGUIoptions`, and `promptSave`.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[getGUIoptions](#), [setGUIoptions](#), [promptWriteOptions](#)

Examples

```
## Not run:
declareGUIOptions("editor")

## End(Not run)
```

doAction

*Execute Action Created by a Widget***Description**

Executes the action expression formulated by the user and written as an ‘action’ by a widget.

Usage

```
doAction(act)
```

Arguments

act string representing an expression that can be executed

Details

If act is missing, doAction looks for it in the action directory of the window’s widget directory in .PBSmod. This action can be accessed through `getWinAct()[1]`.

Due to parsing complications, the expression act must contain the backtick character ‘`’ wherever there is to be an internal double quote ‘”’ character. For example,

```
"openFile(paste(getWinVal()$prefix, '.tpl', sep=' '))"
```

Value

Invisibly returns the string expression act.

Note

The action is

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

Examples

```
createWin("button text=\"list directory files\" func=doAction action=print(ls())", astart=TRUE)
```

drawBars	<i>Draw a Linear Barplot on the Current Plot</i>
----------	--

Description

Draw a linear barplot on the current plot.

Usage

```
drawBars(x, y, width, base = 0, ...)
```

Arguments

x	x-coordinates
y	y-coordinates
width	bar width, computed if missing
base	y-value of the base of each bar
...	further graphical parameters (see par) may also be supplied as arguments

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

Examples

```
plot(0:10,0:10,type="n")
drawBars(x=1:9,y=9:1,col="deepskyblue4",lwd=3)
```

evalCall	<i>Evaluate a Function Call</i>
----------	---------------------------------

Description

Evaluates a function call after resolving potential argument conflicts.

Usage

```
evalCall(fn, argu, ..., envir = parent.frame(),
         checkdef=FALSE, checkpar=FALSE)
```

Arguments

fn	R function
argu	list of explicitly named arguments and their values to pass to fn.
...	additional arguments that a user might wish to pass to fn.
envir	environment from which the call originates (currently has no use or effect).
checkdef	logical: if TRUE, gather additional formal arguments from the functions default function.
checkpar	logical: if TRUE, gather additional graphical arguments from the list object par.

Details

This function builds a call to the specified function and executes it. During the build, optional arguments ... are checked for

- (i) duplication with explicit arguments argu: if any are duplicated, the user-supplied arguments supercede the explicit ones;
- (ii) availability as usable arguments in fn, fn.default if checkdef=TRUE, and par if checkpar=TRUE.

Value

Invisibly returns the string expression of the function call that is passed to eval(parse(text=expr)).

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

See Also

[doAction](#)

expandGraph

Expand the Plot Area by Adjusting Margins

Description

Optimize the plotting region(s) by minimizing margins.

Usage

```
expandGraph(mar=c(4,3,1.2,0.5), mgp=c(1.6,.5,0), ...)
```

Arguments

mar	numerical vector of the form 'c(bottom, left, top, right)' specifying the margins of the plot
mgp	numerical vector of the form 'c(axis title, axis labels, axis line)' specifying the margins for axis title, axis labels, and axis line
...	additional graphical parameters to be passed to par

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

See Also

[resetGraph](#)

Examples

```
resetGraph(); expandGraph(mfrow=c(2,1));
tt=seq(from=-10, to=10, by=0.05);

plot(tt,sin(tt), xlab="this is the x label", ylab="this is the y label",
main="main title", sub="sometimes there is a \"sub\" title")
plot(cos(tt),sin(tt*2), xlab="cos(t)", ylab="sin(2 t)", main="main title",
sub="sometimes there is a \"sub\" title")
```

exportHistory

Export a Saved History

Description

Export the current history list.

Usage

```
exportHistory(hisname="", fname="")
```

Arguments

hisname	name of the history list to export. If set to "", the value from <code>getWinAct()[1]</code> will be used instead.
fname	file name where history will be saved. If it is set to "", a <Save As> window will be displayed.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[importHistory](#), [initHistory](#), [promptSaveFile](#)

findPat *Search a Character Vector to Find Multiple Patterns*

Description

Use all available patterns in pat to search in vec, and return the matched elements in vec.

Usage

```
findPat(pat, vec)
```

Arguments

pat	character vector of patterns to match in vec
vec	character vector where matches are sought

Value

A character vector of all matched strings.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

Examples

```
#find all strings with a vowel, or that start with a number
findPat(c("[aeoiy]", "^[0-9]"), c("hello", "WRLD", "11b"))
```

findPrefix *Find a Prefix Based on Names of Existing Files*

Description

Find the prefixes or suffixes of files with a given suffix or prefix in a directory.

Usage

```
findPrefix(suffix, path=".")
findSuffix(prefix, path=".")
```

Arguments

suffix	character vector of suffixes
prefix	character vector of prefixes
path	directory to look for files in

Details

The function `findPrefix` locates all files in a directory that end with one of the provided suffixes; where as `findSuffix` locates all files that start with the given prefixes.

Value

A character vector of all the prefixes or suffixes of files in the working directory that matched to one of the given suffixes.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

Examples

```
#TODO give better examples from the library's example dir
findPrefix( c(".txt", ".r") )

#or use R's dir for similar functionality
dir(pattern="txt$")
dir(pattern="^[a-h]")
```

findProgram

Locates a program in the PATH environment variable

Description

Returns the complete filename and path of a program in the PATH environment variable. This is a wrapper for `Sys.which`, and may be deprecated in the future.

Usage

```
findProgram( name, includename=FALSE )
```

Arguments

<code>name</code>	name of a program to locate
<code>includename</code>	boolean: if true, include the filename in the path returned, otherwise just the directory.

Value

A string containing the location of the program. NULL is returned if the program is not located.

Author(s)

Alex Couture-Beil

See Also[Sys.which](#)**Examples**

```
findProgram( "gcc" )
findProgram( "notepad" )
findProgram( "R", TRUE )
```

focusWin

*Set the Focus on a Particular Window***Description**

Bring the specified window into focus, and set it as the active window. `focusWin` will fail to bring the window into focus if it is called from the R console, since the R console returns focus to itself once a function returns. However, it will work if `focusWin` is called as a result of calling a function from the GUI window. (i.e., pushing a button or any other widget that has a function argument).

Usage

```
focusWin(winName, winVal=TRUE)
```

Arguments

<code>winName</code>	name of window to focus
<code>winVal</code>	if TRUE, associate <code>winName</code> with the default window for <code>setWinVal</code> and <code>getWinVal</code>

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

Examples

```
## Not run:
focus <- function() {
  winName <- getWinVal()$select;
  focusWin(winName);
  cat("calling focusWin(\"", winName, "\")\n", sep="");
  cat("getWinVal()$myvar = ", getWinVal()$myvar, "\n\n", sep=""); };

#create three windows named win1, win2, win3
#each having three radio buttons, which are used to change the focus
for(i in 1:3) {
  winDesc <- c(
    paste('window name=win',i,' title="Win',i,'" ', sep=''),
    paste('entry myvar ', i, sep=''),
    'radio name=select value=win1 text="one" function=focus mode=character',
    'radio name=select value=win2 text="two" function=focus mode=character',
```

```
'radio name=select value=win3 text="three" function=focus mode=character');  
createWin(winDesc, astext=TRUE); };  
  
## End(Not run)
```

genMatrix

Generate Test Matrices for plotBubbles

Description

Generate a test matrix of random numbers (μ = mean and σ = standard deviation), primarily for plotBubbles.

Usage

```
genMatrix(m,n,mu=0,sigma=1)
```

Arguments

m	number of rows
n	number of columns
mu	mean of normal distribution
sigma	standard deviation of normal distribution

Value

An m by n matrix with normally distributed random values.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

See Also

[plotBubbles](#)

Examples

```
plotBubbles(genMatrix(20,6))
```

getChoice

Choose One String Item from a List of Choices

Description

Prompts the user to choose one string item from a list of choices displayed in a GUI. The simplest case `getChoice()` yields TRUE or FALSE.

Usage

```
getChoice(choice=c("Yes","No"), question="Make a choice: ",
          winname="getChoice", horizontal=TRUE, radio=FALSE,
          qcolor="blue", gui=FALSE, quiet=FALSE)
```

Arguments

choice	vector of strings from which to choose.
question	question or prompting statement.
winname	window name for the <code>getChoice</code> GUI.
horizontal	logical: if TRUE, display the choices horizontally, else vertically.
radio	logical: if TRUE, display the choices as radio buttons, else as buttons.
qcolor	colour for question.
gui	logical: if TRUE, <code>getChoice</code> is functional when called from a GUI, else it is functional from command line programs.
quiet	logical: if TRUE, don't print the choice on the command line.

Details

The user's choice is stored in `.PBSmod$options$getChoice` (or whatever `winname` is supplied). `getChoice` generates an `onClose` function that returns focus to the calling window (if applicable) and prints out the choice.

Value

If called from a GUI (`gui=TRUE`), no value is returned directly. Rather, the choice is written to the PBS options workspace, accessible through `getPBSoptions("getChoice")` (or whatever `winname` was supplied).

If called from a command line program (`gui=FALSE`), the choice is returned directly as a string scalar (e.g., `answer <- getChoice(gui=F)`).

Note

Microsoft Windows users may experience difficulties switching focus between the R console and GUI windows. The latter frequently disappear from the screen and need to be reselected (either clicking on the task bar or pressing `<Alt><Tab>`). This issue can be resolved by switching from MDI to SDI mode. From the R console menu bar, select `<Edit>` and `<GUI preferences>`, then change the value of "single or multiple windows" to SDI.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

See Also

[chooseWinVal](#), [getWinVal](#), [setWinVal](#)

Examples

```
## Not run:
#-- Example 1
getChoice(c("Fame", "Fortune", "Health", "Beauty", "Lunch"),
  "What do you want?", qcolor="red", gui=F)

#-- Example 2
getChoice(c("Homer Simpson", "Wilberforce Humphries", "Miss Marple"),
  "Who's your idol?", horiz=F, radio=T, gui=F)

## End(Not run)
```

getGUIOptions

Get PBS Options for Widgets

Description

Get the PBS options declared for GUI usage and set their corresponding widget values.

Usage

```
getGUIOptions()
```

Details

The options declared using `declareGUIOptions` are copied from the R environment into widget values. These widgets should have names that match the names of their corresponding options.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[declareGUIOptions](#), [setGUIOptions](#), [promptWriteOptions](#), [readPBSOptions](#)

Examples

```
## Not run:
getPBSOptions() #loads from default PBSOptions.txt

## End(Not run)
```

`getOptions`*Get and Set User Options*

Description

Functions to get and set user options within an option class object.

Usage

```
getOptions(option.object, key)
setOptions(option.object, ...)
```

Arguments

<code>option.object</code>	options class object used for storing package options
<code>...</code>	any number of user options to set, where the named argument is the option key and the value is the option value
<code>key</code>	name of option to retrieve – if missing all options are returned

Value

`getOptions`: returns the value of the option specified by key.
If key is missing, a list of all options.

Author(s)

Alex Couture-Beil

See Also

See [PBSoptions-class](#) for more details and an example using **PBSmodelling**'s option management functions.

`getOptionsFileName`*Get and Set File Name for Saving and Loading of Options*

Description

Functions for retrieving and setting the default file name used by `loadOptions` and `saveOptions`.

Usage

```
getOptionsFileName(option.object)
setOptionsFileName(option.object, name)
```

Arguments

option.object options class object used for storing package options
name new name for default file name

Value

getOptionsFileName: the default file name

See Also

[loadOptions](#), [saveOptions](#)

See [PBSoptions-class](#) for more details and an example using **PBSmodelling**'s option management functions.

getOptionsPrefix *Get and Set GUI Prefix of Options Class*

Description

The GUI prefix is used for determining which GUI variables are associated with a user option.

Usage

```
getOptionsPrefix(option.object)  
setOptionsPrefix(option.object, prefix)
```

Arguments

option.object options class object used for storing package options
prefix new prefix to use

Value

getOptionsPrefix: a prefix string used to reference GUI variables

See Also

See [PBSoptions-class](#) for more details and an example using **PBSmodelling**'s option management functions.

Examples

```
.mypkg <<- new( "PBSoptions", filename="my_pkg.txt",
  initial.options=list(pi=3.14), gui.prefix="opt" )

#prefix the option "pi" with "opt" to get "optpi"
createWin( "entry name=optpi", astatic = TRUE )

#the GUI variable "optpi" will be loaded with the option "pi"
loadOptionsGUI( .mypkg )
```

getPBSext

Get a Command Associated With a File Name

Description

Display all locally defined file extensions and their associated commands, or search for the command associated with a specific file extension ext.

Usage

```
getPBSext(ext)
```

Arguments

ext optional string specifying a file extension.

Value

Command associated with file extension.

Note

These file associations are not saved from one *PBS Modelling* session to the next unless explicitly saved and loaded (see `writePBSoptions` and `readPBSoptions`).

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[setPBSext](#), [openFile](#), [clearPBSext](#)

getPBSoptions	<i>Retrieve A User Option</i>
---------------	-------------------------------

Description

Get a previously defined user option.

Usage

```
getPBSoptions(option)
```

Arguments

option name of option to retrieve. If omitted, a list containing all options is returned.

Value

Value of the specified option, or NULL if the specified option is not found.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[getPBSext](#), [readPBSoptions](#)

getWinAct	<i>Retrieve the Last Window Action</i>
-----------	--

Description

Get a string vector of actions (latest to earliest).

Usage

```
getWinAct(winName)
```

Arguments

winName name of window to retrieve action from

Details

When a function is called from a GUI, a string descriptor associated with the action of the function is stored internally (appended to the first position of the action vector). A user can utilize this action as a type of argument for programming purposes. The command `getWinAct()[1]` yields the latest action.

Value

String vector of recorded actions (latest first).

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

getWinFun

Retrieve Names of Functions Referenced in a Window

Description

Get a vector of all function names referenced by a window.

Usage

```
getWinFun(winName)
```

Arguments

winName name of window, to retrieve its function list

Value

A vector of function names referenced by a window.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

getWinVal

Retrieve Widget Values for Use in R Code

Description

Get a list of variables defined and set by the GUI widgets. An optional argument scope directs the function to create local or global variables based on the list that is returned.

Usage

```
getWinVal(v=NULL, scope="", asvector=FALSE, winName="")
```

Arguments

v	vector of variable names to retrieve from the GUI widgets. If NULL, v retrieves all variables from all GUI widgets.
scope	scope of the retrieval. The default sets no variables in the non-GUI environment; scope="L" creates variables locally in relation to the parent frame that called the function; and scope="G" creates global variables(pos=1).
asvector	return a vector instead of a list. WARNING: if a widget variable defines a true vector or matrix, this will not work.
winName	window from which to select GUI widget values. The default takes the window that has most recently received new user input.

Details

TODO talk about scope=G/L and side effects of overwriting existing variables

Value

A list (or vector) with named components, where names and values are defined by GUI widgets.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[parseWinFile](#), [setWinVal](#), [clearWinVal](#)

getYes

Prompt the User to Choose Yes or No

Description

Display a message prompt with "Yes" and "No" buttons.

Usage

```
getYes(message, title="Choice", icon="question")
```

Arguments

message	message to display in prompt window.
title	title of prompt window.
icon	icon to display in prompt window; options are "error", "info", "question", or "warning".

Value

Returns TRUE if the "Yes" button is clicked, FALSE if the "No" button is clicked.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[showAlert](#), [getChoice](#), [chooseWinVal](#)

Examples

```
## Not run:
#default settings
if(getYes("Print the number 1?"))
  print(1)

## End(Not run)
```

 GT0

Restrict a Numeric Variable to a Positive Value

Description

Restrict a numeric value x to a positive value using a differentiable function. GT0 stands for “greater than zero”.

Usage

```
GT0(x, eps=1e-4)
```

Arguments

x	vector of values
eps	minimum value greater than zero.

Details

```
if (x >= eps).....GT0 = x
if (0 < x < eps).....GT0 = (eps/2) * (1 + (x/eps)^2)
if (x <= 0).....GT0 = eps/2
```

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

See Also

[scalePar](#), [restorePar](#), [calcMin](#)

Examples

```
plotGT0 <- function(eps=1,x1=-2,x2=10,n=1000,col="black") {
  x <- seq(x1,x2,len=n); y <- GT0(x,eps);
  lines(x,y,col=col,lwd=2); invisible(list(x=x,y=y)); }

testGT0 <- function(eps=c(7,5,3,1,.1),x1=-2,x2=10,n=1000) {
  x <- seq(x1,x2,len=n); y <- x;
  plot(x,y,type="l");
  mycol <- c("red","blue","green","brown","violet","orange","pink");
  for (i in 1:length(eps))
  plotGT0(eps=eps[i],x1=x1,x2=x2,n=n,col=mycol[i]);
  invisible(); };

testGT0()
```

importHistory

Import a History List from a File

Description

Import a history list from file `fname`, and place it into the history list `hisname`.

Usage

```
importHistory(hisname="", fname="", updateHis=TRUE)
```

Arguments

<code>hisname</code>	name of the history list to be populated. The default ("") uses the value from <code>getWinAct()[1]</code> .
<code>fname</code>	file name of history file to import. The default ("") causes an open-file window to be displayed.
<code>updateHis</code>	logical: if TRUE, update the history widget to reflect the change in size and index.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[exporthistory](#), [inithistory](#), [promptOpenFile](#)

initHistory

Create Structures for a New History Widget

Description

PBS history functions (below) are available to those who would like to use the package's history functionality, without using the pre-defined history widget. These functions allow users to create customized history widgets.

Usage

```

initHistory(hisname, indexname=NULL, sizename=NULL,
            buttonnames=NULL, modename=NULL, func=NULL, overwrite=TRUE)
rmHistory(hisname="", index="")
addHistory(hisname="")
forwHistory(hisname="")
backHistory(hisname="")
lastHistory(hisname="")
firstHistory(hisname="")
jumpHistory(hisname="", index="")
clearHistory(hisname="")

```

Arguments

hisname	name of the history "list" to manipulate. If it is omitted, the function uses the value of <code>getWinAct()[1]</code> as the history name. This allows the calling of functions directly from the <i>window description file</i> (except <code>initHistory</code> , which must be called before <code>createWin()</code>).
indexname	name of the index entry widget in the <i>window description file</i> . If <code>NULL</code> , then the current index feature will be disabled.
sizename	name of the current size entry widget. If <code>NULL</code> , then the current size feature will be disabled.
buttonnames	named list of names of the first, prev, next, and last buttons. If <code>NULL</code> , then the buttons are not disabled ever
modename	name of the radio widgets used to change <code>addHistory</code> 's mode. If <code>NULL</code> , then the default mode will be to insert after the current index.
index	index to the history item. The default (<code>""</code>) causes the value to be extracted from the widget identified by <code>indexname</code> .
func	name of user supplied function to call when viewing history items.
overwrite	if <code>TRUE</code> , history (matching <code>hisname</code>) will be cleared. Otherwise, the imported history will be merged with the current one.

Details

PBS Modelling includes a pre-built history widget designed to collect interesting choices of GUI variables so that they can be redisplayed later, rather like a slide show.

Normally, a user would invoke a history widget simply by including a reference to it in the *window description file*. However, PBS Modelling includes support functions (above) for customized applications.

To create a customized history, each button must be described separately in the *window description file* rather than making reference to the history widget.

The history "List" must be initialized before any other functions may be called. The use of a unique history name (hisname) is used to associate a unique history session with the supporting functions.

The indexname and sizename arguments correspond to the given names of entry widgets in the *window description file*, which will be used to display the current index and total size of the list. The indexname entry widget can also be used by jumpHistory to retrieve a target index.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[importHistory](#), [exportHistory](#)

Examples

```
## Not run:
# Example of creating a custom history widget that saves values
# whenever the "Plot" button is pressed. The user can tweak the
# inputs "a", "b", and "points" before each "Plot" and see the
# "Index" increase. After sufficient archiving, the user can review
# scenarios using the "Back" and "Next" buttons.
# A custom history is needed to achieve this functionality since
# the packages pre-defined history widget does not update plots.

# To start, create a Window Description to be used with createWin
# using astext=TRUE. P.S. Watch out for special characters which
# must be "escaped" twice (first for R, then PBSmodelling).

winDesc <- '
window title="Custom History"
vector names="a b k" labels="a b points" font="bold" \\
values="1 1 1000" function=myPlot
grid 1 3
button function=myHistoryBack text="<- Back"
button function=myPlot text="Plot"
button function=myHistoryForw text="Next ->"
grid 2 2
label "Index"
entry name="myHistoryIndex" width=5
label "Size"
```

```
entry name="myHistorySize" width=5
,
# Convert text to vector with each line represented as a new element
winDesc <- strsplit(winDesc, "\n")[[1]]

# Custom functions to update plots after restoring history values
myHistoryBack <- function() {
  backHistory("myHistory");
  myPlot(saveVal=FALSE); # show the plot with saved values
}
myHistoryForw <- function() {
  forwHistory("myHistory");
  myPlot(saveVal=FALSE); # show the plot with saved values
}
myPlot <- function(saveVal=TRUE) {
  # save all data whenever plot is called (directly)
  if (saveVal) addHistory("myHistory");
  getWinVal(scope="L");
  tt <- 2*pi*(0:k)/k;
  x <- (1+sin(a*tt)); y <- cos(tt)*(1+sin(b*tt));
  plot(x, y);
}

initHistory("myHistory", "myHistoryIndex", "myHistorySize")
createWin(winDesc, astext=TRUE)

## End(Not run)
```

isWhat

Identify an Object and Print Information

Description

Identify an object by class, mode, typeof, and attributes.

Usage

```
isWhat(x)
```

Arguments

x an R object

Value

No value is returned. The function prints the object's characteristics on the command line.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

loadC

*Launch a GUI for Compiling and Loading C Code***Description**

A GUI interface allows users to edit, compile, and embed C functions in the R environment.

Usage

loadC()

Details

The function loadC() launches an interactive GUI that can be used to manage the construction of C functions intended to be called from R. The GUI provides tools to edit, compile, load, and run C functions in the R environment.

The loadC GUI also includes a tool for comparison between the running times and return values of R and C functions. It is assumed that the R and C functions are named `prefix.r` and `prefix.c`, respectively, where `prefix` can be any user-chosen prefix. If an initialization function `prefix.init` exists, it is called before the start of the comparison.

The GUI controls:

File Prefix	Prefix for .c and .r files.
Lib Prefix	Prefix for shared library object.
Set WD	Set the working directory.
Open Log	Open the log file.
Open.c File	Open the file <code>prefix.c</code> from the working directory.
Open.r File	Open the file <code>prefix.r</code> from the working directory.
COMPILE	Compile <code>prefix.c</code> into a shared library object.
LOAD	Load the shared library object.
SOURCE R	Source the file <code>prefix.r</code> .
UNLOAD	Unload the shared library object.
Options	
Editor	Text editor to use.
Update	Commit option changes.
Browse	Browse for a text editor.
Clean Options	
Select All	Select all check boxes specifying file types.
Select None	Select none of the check boxes.
Clean Proj	Clean the project of selected file types.
Clean All	Clean the directory of selected file types.
Comparison	
Times to Run	Number of times to run the R and C functions.
RUN	Run the comparison between R and C functions.
R Time	Computing time to run the R function multiple times.
C Time	Computing time to run the C function multiple times.
Ratio	Ratio of R/C run times.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[compileC](#)

loadOptions	<i>Save and Load Options to and from Disk</i>
-------------	---

Description

Save and load options for use from one R session to another. If no file name is given, then the default file name (specified when the option object was created) is used.

Usage

```
loadOptions(option.object, fname, prompt = FALSE)
saveOptions(option.object, fname, prompt = FALSE)
```

Arguments

option.object	options class object used for storing package options
fname	file name to use: if missing the default file name is used; if given, file name becomes the default.
prompt	logical: if TRUE, prompt the user to select a file from an interactive GUI. If fname is given, then the value appears as the default selected file.

Details

If fname is given (or selected when prompt=TRUE), then that file becomes the default file name for subsequent loading and saving.

See Also

See [PBSoptions-class](#) for more details and an example using **PBSmodelling**'s option management functions.

loadOptionsGUI

Load and Save Options Values to and from a GUI

Description

These functions are used to move option values to and from a GUI. Option values are stored within an R object (as referenced by the `option.object`).

`loadOptionsGUI` copies the values from the R object to the GUI.

`saveOptionsGUI` copies the GUI values from the tcltk GUI to the R object.

Usage

```
loadOptionsGUI(option.object)
```

```
saveOptionsGUI(option.object)
```

Arguments

`option.object` options class object used for storing package options

See Also

See [PBSoptions-class](#) for more details and an example using **PBSmodelling**'s option management functions.

openExamples*Open Example Files from a Package*

Description

Open examples from the examples subdirectory of a given package.

Usage

```
openExamples(package, prefix, suffix)
```

Arguments

`package` name of the package that contains the examples.

`prefix` prefix of the example file(s).

`suffix` character vector of suffixes for the example files.

Details

Copies of each example file are placed in the working directory and opened. If files with the same name already exist, the user is prompted with a choice to overwrite.

To use this function in a *window description file*, the package, prefix and suffix arguments must be specified as the action of the widget that calls openExamples. Furthermore, package, prefix, and each suffix must be separated by commas. For example, action=myPackage,example1,.r,.c will copy example1.r and example2.c from the examples directory of the package **myPackage** to the working directory and open these files. If the function was called by a widget, a widget named prefix will be set to the specified prefix.

Note

If all the required arguments are missing, it is assumed that the function is being called by a GUI widget.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[openFile](#), [openProjFiles](#), [openPackageFile](#)

Examples

```
## Not run:  
# Copies example1.c and example2.r from the examples directory in  
# myPackage to the working directory, and opens these files  
openExamples("myPackage", "example1", c(".r", ".c"))  
  
## End(Not run)
```

openFile

Open a File with an Associated Program

Description

Open a file using the program associated with its extension defined by the Windows shell. Non-windows users, or users wishing to override the default application, can specify a program association using setPBSext.

Usage

```
openFile(fname, package=NULL)
```

Arguments

fname	name(s) of file(s) to open.
package	(optional) open files relative to this package

Value

An invisible string vector of the file names and/or commands + file names.

Warning

Windows only: `openFile("..")` does not work as expected, but `openFile("../..")` only opens the first parent directory.

Note

If a command is registered with `setPBSext`, then `openFile` will replace all occurrences of `"%f"` with the absolute path of the filename, before executing the command.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[getPBSext](#), [setPBSext](#), [clearPBSext](#), [writePBSoptions](#)

Examples

```
## Not run:

#use openFile directly:
openFile( "doc/PBSmodelling-UG.pdf", package="PBSmodelling" )

#via doAction in a window description file:
createWin( "button text=help func=doAction action=\"openFile( 'doc/PBSmodelling-UG.pdf', package='PBSmodelling' )" )

#####
# Set up firefox to open .html files (only applicable if firefox is NOT the default web browser
setPBSext("html", "'c:/Program Files/Mozilla Firefox/firefox.exe" file://%f')
openFile("foo.html")

## End(Not run)
```

openPackageFile	<i>Open a File from a Package Subdirectory</i>
-----------------	--

Description

Open a file from a package in the R library, given the package name and the file path relative to the package root directory.

Usage

```
openPackageFile(package, filepath)
```

Arguments

package	name of the package
filepath	path to file from the package's root directory

Details

The `openFile` function is used to open the file, using associations set by `setPBSext`.

To use this function in a *window description file*, the `package` and `filepath` arguments must be specified as the action of the widget that calls `openPackageFile`. Furthermore, `package` and `filepath` must be separated by commas (e.g., `action=myPackage,/doc/help.pdf`).

If all the required arguments are missing, it is assumed that the function is being called by a GUI widget.

Note

*** This function is deprecated and will be removed in a future version. Use [openFile](#) or [doAction](#) with `openFile`. ***

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[openFile](#), [setPBSext](#), [openProjFiles](#), [openExamples](#)

Examples

```
## Not run:  
#use openFile directly:  
openFile( "doc/PBSmodelling-UG.pdf", package="PBSmodelling" )  
  
#via doAction in a window description file:  
createWin( "button text=help func=doAction action=\"openFile( 'doc/PBSmodelling-UG.pdf', package='PBSmodelling' )"
```

```
## End(Not run)
```

openProjFiles

Open Files with a Common Prefix

Description

Open one or more files from the working directory, given one file prefix and one or more file suffixes.

Usage

```
openProjFiles(prefix, suffix, package=NULL, warn=NULL, alert=TRUE)
```

Arguments

prefix	a single prefix to prepend to each suffix
suffix	a character vector of suffixes to append to the prefix
package	name of the package that contains templates, or NULL to not use templates
warn	if specified, use to temporarily override the current R warn option during this function's activity; if NULL, the current warning settings are used.
alert	if TRUE, an alert message is shown should any files fail to be opened; if FALSE, no alert is displayed.

Details

The suffixes may contain wildcards ("*" to match 0 or more characters, "?" to match any single character).

For any file that does not exist in the working directory, a template can optionally be copied from a directory named `templates` in the specified package. The templates in this directory should have the prefix `template`, followed by the suffix to match when `openProjFiles` is called (e.g., `template.c` to match the suffix `.c`). After being copied to the working directory, the new file is renamed to use the specified prefix.

To use this function in a *window description file*, the `package` and `suffix` arguments must be specified as the action of the widget that calls `openProjFiles`. Furthermore, `package` and each `suffix` must be separated by commas. For example, `action=myPackage, .r, .c` will try to open a `.r` and `.c` file in the working directory, copying templates from the `template` directory for the package **myPackage**, if the files didn't already exist. To disable templates, leave `package` unspecified but keep the leading comma (e.g., `action=, .r, .c`). When the function is called from a widget in this fashion, the prefix is taken from the value of a widget named `prefix`.

If all the required arguments are missing, it is assumed that the function is being called by a GUI widget.

Note

*** This function is deprecated and will be removed in a future version. Use [openFile](#) or [doAction](#) with `openFile`. ***

*** Warning: this function is buggy; see examples for an alternative. ***

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[openFile](#), [setPBSext](#), [openExamples](#), [openPackageFile](#)

Examples

```
## Not run:
openProjFiles("foo", c(".r", ".c"), package="myPackage")

#use openFile directly:
openFile( dir(pattern="^prefix.*\\.suffix$") )

#example with multiple suffixes (prefix=foo, suffix=.r, .c)
openFile( dir(pattern="^foo.*\\.(r|c)$") )

## End(Not run)
```

openUG

Open Package User Guide

Description

Open package User's Guide 'pkg-UG.pdf' if it exists. This function is essentially a wrapper for `codeopenFile`.

Usage

```
openUG(pkg = "PBSmodelling")
```

Arguments

pkg Full name (with or without quotes) of a package installed on the user's system.

Details

We assume that the name of the User's Guide follows 'PBS' conventions. This means a user's guide in PDF format with extension pdf. The name of the PDF file will be '<pkg>-UG.pdf' (e.g., PBSmodelling-UG.pdf).

Author(s)

Rowan Haigh, Pacific Biological station, Nanaimo BC

See Also

[openFile](#), [showHelp](#), [viewCode](#)

packList	<i>Pack a List with Objects</i>
----------	---------------------------------

Description

Pack a list with existing objects using names only.

Usage

```
packList(stuff, target="PBSlist", value,  
         lenv=parent.frame(), tenv=.GlobalEnv)
```

Arguments

stuff	string vector of object names
target	target list object
value	an optional explicit value to assign to stuff
lenv	local environment where objects are located
tenv	target environment where target list is or will be located

Details

A list object called target will be located in the tenv environment. The objects named in stuff and located in the lenv environment will appear as named components within the list object target.

If an explicit value is specified, the function uses this value instead of looking for local objects. Essentially, stuff=value which is then packed into target.

Value

No value is returned

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

See Also

[unpackList](#), [readList](#), [writeList](#)

Examples

```
fn = function() {  
  alpha=rnorm(10)  
  beta=letters  
  gamma=mean  
  delta=longley  
  packList(c("alpha", "beta", "gamma", "delta")) }  
fn(); print(PBSlist)
```

pad0

Pad Numbers with Leading Zeroes

Description

Convert numbers to integers then text, and pad them with leading zeroes.

Usage

```
pad0(x, n, f = 0)
```

Arguments

x	vector of numbers
n	number of text characters representing a padded integer
f	factor of 10 transformation on x before padding

Value

A character vector representing x with leading zeroes.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

Examples

```
resetGraph(); x <- pad0(x=123,n=10,f=0:7);  
addLabel(.5, .5,paste(x,collapse="\n"),cex=1.5);
```

`parseWinFile`*Convert a Window Description File into a List Object*

Description

Parse a *window description file* (markup file) into the list format expected by `createWin`.

Usage

```
parseWinFile(fname, astext=FALSE)
```

Arguments

<code>fname</code>	file name of the <i>window description file</i> .
<code>astext</code>	if TRUE, <code>fname</code> is interpreted as a vector of strings, with each element representing a line of code in a <i>window description file</i> .

Value

A list representing a parsed *window description file* that can be directly passed to `createWin`.

Note

All widgets are forced into a 1-column by N-row grid.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[createWin](#), [compileDescription](#)

Examples

```
## Not run:  
x<-parseWinFile(system.file("examples/LissFigWin.txt",package="PBSmodelling"))  
createWin(x)  
  
## End(Not run)
```

pause

Pause Between Graphics Displays or Other Calculations

Description

Pause, typically between graphics displays. Useful for demo purposes.

Usage

```
pause(s = "Press <Enter> to continue")
```

Arguments

s text issued on the command line when pause is invoked.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

PBSmodelling

PBS Modelling

Description

PBS Modelling provides software to facilitate the design, testing, and operation of computer models. It focuses particularly on tools that make it easy to construct and edit a customized graphical user interface (GUI). Although it depends heavily on the R interface to the Tcl/Tk package, a user does not need to know Tcl/Tk.

PBSmodelling contains examples that illustrate models built using other R packages, including PBSmapping, odesolve, PBSddesolve, and BRugs. It also serves as a convenient prototype for building new R packages, along with instructions and batch files to facilitate that process.

The R directory `.../library/PBSmodelling/doc` includes a complete user guide ‘PBSmodelling-UG.pdf’. To use this package effectively, please consult the guide.

PBS Modelling comes packaged with interesting examples accessed through the function `runExamples()`. Additionally, users can view *PBS Modelling* widgets through the function `testWidgets()`. More generally, a user can run any available demos in his/her locally installed packages through the function `runDemos()`.

 PBSoptions-class *Project Options Class*

Description

Projects commonly involve various settings or options such as paths to C compilers or other third-party tools. **PBSmodelling** provides a set of option management functions for managing user specific options. Options can be modified through the provided set of functions on the command line, or through a custom GUI. These options can be saved to disk for use in subsequent R sessions.

To use **PBSmodelling**'s suite of option management functions, a PBSoptions object must be created for each of your projects. Each PBSoptions object contains a distinct R environment where option values are stored; this allows different projects to use overlapping option names without conflicts (provided each project has its own PBSoptions class object).

Details

When a PBSoptions object is created with the new function, the `initial.options` list, if supplied, is stored as initial user options in the object. The initialization routine then attempts to load user set options from the `filename` file. If such a file exists, these values are stored in the PBSoptions object overwriting any initial values as specified by `initial.options`

Option values are not directly stored in the object, but rather in an environment stored in the instance slot. Using an environment rather than slots for storing options allows us to pass option object by reference rather than value; that is, we can save options in the object without the need of returning a new modified class object. It is therefore necessary that users use the functions listed in the "see also" section to effectively manage user options.

Objects from the Class

Objects can be created by calls of the form
`new("PBSoptions", filename, initial.options=list(), gui.prefix="option")`.

`filename`: default file name to use when saving and loading options to and from disk

`initial.options`: a list with distinctly named initial options to use if no previously saved file exists

`gui.prefix`: a prefix used to identify GUI variables which correspond to user options

Slots

`instance`: The R environment used to store options. Please do not use this directly; use the functions listed under the "see also" section.

Methods

print `signature(x = "PBSoptions")`: prints the list of options

Warning

Do not use the slots – use the access functions instead.

Author(s)

Alex Couture-Beil

See Also

[getOptions](#) for retrieving and modifying user options

[getOptionsFileName](#) for retrieving and modifying the default options file name

[loadOptions](#) for loading and saving options from and to disk

[getOptionsPrefix](#) for retrieving and modifying the GUI prefix (for custom GUI interfaces)

[loadOptionsGUI](#) for setting GUI values to reflect user options and vice-versa

Examples

```
#initialize an option manager with a single logical option
.mypkg <<- new( "PBSoptions", filename="my_pkg.txt",
  initial.options=list( sillyhatday=FALSE ) )

#retrieving an option
silly <- getOptions( .mypkg, "sillyhatday" )
cat( "today is", ifelse( silly, "silly hat day!", "monday" ), "\n" )

#set an option
setOptions( .mypkg, sillyhatday = TRUE, photos = "/shares/silly_hat_photos" )

#create a GUI which works with options
createWin( c(
  "check name=optionsillyhatday text=\"silly hat day\"",
  "entry name=optionphotos mode=character label=\"photos directory\"",
  "button func=doAction text=save action=saveOptionsGUI(.mypkg)" ), astext = TRUE )

#update GUI values based on values stored in .mypkg's options
loadOptionsGUI( .mypkg )
print(getOptions( .mypkg ))
```

pickCol

Pick a Colour From a Palette and get the Hexadecimal Code

Description

Display an interactive colour palette from which the user can choose a colour.

Usage

```
pickCol(returnValue=TRUE)
```

Arguments

returnValue If TRUE, display the full colour palette, choose a colour, and return the hex value to the R session.
If FALSE, use an intermediate GUI to interact with the palette and display the hex value of the chosen colour.

Value

A hexadecimal colour value.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[testCol](#)

Examples

```
## Not run:  
junk<-pickCol(); resetGraph(); addLabel(.5,.5,junk,cex=4,col=junk);  
  
## End(Not run)
```

plotACF

Plot Autocorrelation Bars From a Data Frame, Matrix, or Vector

Description

Plot autocorrelation bars (ACF) from a data frame, matrix, or vector.

Usage

```
plotACF(file, lags=20,  
        clrs=c("blue","red","green","magenta","navy"), ...)
```

Arguments

file data frame, matrix, or vector of numeric values.
lags maximum number of lags to use in the ACF calculation.
clrs vector of colours. Patterns are repeated if the number of fields exceed the length of clrs.
... additional arguments for plot or lines.

Details

This function is designed primarily to give greater flexibility when viewing results from the R-package BRugs. Use `plotACF` in conjunction with `samplesHistory("*, beg=0, plot=FALSE)` rather than `samplesAutoC` which calls `plotAutoC`.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

Examples

```
resetGraph(); plotACF(trees, lwd=2, lags=30);
```

plotAsp

Construct a Plot with a Specified Aspect Ratio

Description

Plot x and y coordinates using a specified aspect ratio.

Usage

```
plotAsp(x, y, asp=1, ...)
```

Arguments

x	vector of x-coordinate points in the plot.
y	vector of y-coordinate points in the plot.
asp	y/x aspect ratio.
...	additional arguments for plot.

Details

The function `plotAsp` differs from `plot(x, y, asp=1)` in the way axis limits are handled. Rather than expand the range, `plotAsp` expands the margins through padding to keep the aspect ratio accurate.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

Examples

```
x <- seq(0,10,0.1)
y <- sin(x)
par(mfrow=2:1)
plotAsp(x,y,asp=1,xlim=c(0,10),ylim=c(-2,2), main="sin(x)")
plotAsp(x,y^2,asp=1,xlim=c(0,10),ylim=c(-2,2), main="sin^2(x)")
```

plotBubbles

Construct a Bubble Plot from a Matrix

Description

Construct a bubble plot for a matrix *z*.

Usage

```
plotBubbles(z, xval=FALSE, yval=FALSE, dnam=FALSE, rpro=FALSE,
            cpro=FALSE, rres=FALSE, cres=FALSE, powr=0.5, size=0.2, lwd=1,
            clr=c("black","red","blue"), hide0=FALSE, frange=0.1, prettyaxis=FALSE, ...)
```

Arguments

<i>z</i>	input matrix, array (2 dimensions) or data frame.
<i>xval</i>	x-values and/or labels for the columns of <i>z</i> . if <i>xval</i> =TRUE, the first row contains x-values for the columns.
<i>yval</i>	y-values and/or labels for the rows of <i>z</i> . If <i>yval</i> =TRUE, the first column contains y-values for the rows.
<i>dnam</i>	logical: if TRUE, attempt to use dimnames of input matrix <i>z</i> as <i>xval</i> and <i>yval</i> . The dimnames are converted to numeric values and must be strictly increasing or decreasing. If successful, these values will overwrite previously specified values of <i>xval</i> and <i>yval</i> or any default indices.
<i>rpro</i>	logical: if TRUE, convert rows to proportions.
<i>cpro</i>	logical: if TRUE, convert columns to proportions.
<i>rres</i>	logical: if TRUE, use row residuals (subtract row means).
<i>cres</i>	logical: if TRUE, use column residuals (subtract column means).
<i>powr</i>	power transform. Radii are proportional to z^{powr} . Note: <i>powr</i> =0.5 yields bubble areas proportional to <i>z</i> .
<i>size</i>	size (inches) of the largest bubble.
<i>lwd</i>	line width for drawing circles.
<i>clr</i>	colours (3-element vector) used for positive, negative, and zero values, respectively.
<i>hide0</i>	logical: if TRUE, hide zero-value bubbles.
<i>frange</i>	number specifying the fraction by which the range of the axes should be extended.
<i>prettyaxis</i>	logical: if TRUE, apply the pretty function to both axes.
...	additional arguments for plotting functions.

Details

The function `plotBubbles` essentially flips the `z` matrix visually. The columns of `z` become the `x`-values while the rows of `z` become the `y`-values, where the first row is displayed as the bottom `y`-value and the last row is displayed as the top `y`-value. The function's original intention was to display proportions-at-age vs. year.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

See Also

[genMatrix](#)

Examples

```
plotBubbles(round(genMatrix(40,20),0),clrs=c("green","grey","red"));

data(CCA.qbr)
plotBubbles(CCA.qbr,cpro=TRUE,powr=.5,dnam=TRUE,size=.15,
  ylim=c(0,70),xlab="Year",ylab="Quillback Rockfish Age")
```

plotCsum

Plot Cumulative Sum of Data

Description

Plot the cumulative frequency of a data vector or matrix, showing the median and mean of the distribution.

Usage

```
plotCsum(x, add = FALSE, ylim = c(0, 1), xlab = "Measure",
  ylab = "Cumulative Proportion", ...)
```

Arguments

<code>x</code>	vector or matrix of numeric values.
<code>add</code>	logical: if TRUE, add the cumulative frequency curve to a current plot.
<code>ylim</code>	limits for the y-axis.
<code>xlab</code>	label for the x-axis.
<code>ylab</code>	label for the y-axis.
<code>...</code>	additional arguments for the plot function.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

Examples

```
x <- rgamma(n=1000, shape=2)
plotCsum(x)
```

plotDens*Plot Density Curves from a Data Frame, Matrix, or Vector*

Description

Plot the density curves from a data frame, matrix, or vector. The mean density curve of the data combined is also shown.

Usage

```
plotDens(file, clrs=c("blue", "red", "green", "magenta", "navy"), ...)
```

Arguments

file	data frame, matrix, or vector of numeric values.
clrs	vector of colours. Patterns are repeated if the number of fields exceed the length of clrs.
...	additional arguments for plot or lines.

Details

This function is designed primarily to give greater flexibility when viewing results from the R-package BRugs. Use plotDens in conjunction with samplesHistory("*", beg=0, plot=FALSE) rather than samplesDensity which calls plotDensity.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

Examples

```
z <- data.frame(y1=rnorm(50, sd=2), y2=rnorm(50, sd=1), y3=rnorm(50, sd=.5))
plotDens(z, lwd=3)
```

`plotFriedEggs`*Render a Pairs Plot as Fried Eggs and Beer*

Description

Create a pairs plot where the lower left half comprises either fried egg contours or smoke ring contours, the upper right half comprises glasses of beer filled to the correlation point, and the diagonals show frequency histograms of the input data.

Usage

```
plotFriedEggs(A, eggs=TRUE, rings=TRUE, levs=c(0.01,0.1,0.5,0.75,0.95),  
             pepper=200, replace=FALSE, jitt=c(1,1), bw=25, histclr=NULL)
```

Arguments

<code>A</code>	data frame or matrix for use in a pairs plot.
<code>eggs</code>	logical: if TRUE, fry eggs in the lower panels.
<code>rings</code>	logical: if TRUE, blow smoke rings in the lower panels.
<code>levs</code>	explicit contour levels expressed as quantiles.
<code>pepper</code>	number of samples to draw from A to pepper the plots.
<code>replace</code>	logical: if TRUE, sample A with replacement.
<code>jitt</code>	argument factor used by function base: <code>: jitter</code> when peppering. If user supplies two numbers, the first will jitter x, the second will jitter y.
<code>bw</code>	argument bandwidth used by function <code>KernSmooth: :bkde2D</code> .
<code>histclr</code>	user-specified colour(s) for histogram bars along the diagonal.

Details

This function comes to us from Dr. Steve Martell of the Fisheries Science Centre at UBC. Obviously many hours of contemplation with his students at the local pub have contributed to this unique rendition of a pairs plot.

Note

If `eggs=TRUE` and `rings=FALSE`, fried eggs are served.
If `eggs=FALSE` and `rings=TRUE`, smoke rings are blown.
If `eggs=TRUE` and `rings=TRUE`, only fried eggs are served.
If `eggs=FALSE` and `rings=FALSE`, only pepper is sprinkled.

Author(s)

Steve Martell, University of British Columbia, Vancouver BC

See Also

[plotBubbles](#), [scalePar](#)

`KernSmooth::bkde2D`, `grDevices::contourLines`, `graphics::contour`

Examples

```
x=rnorm(5000,10,3); y=-x+rnorm(5000,1,4); z=x+rnorm(5000,1,3)
A=data.frame(x=x,y=y,z=z)
for (i in 1:3)
  switch(i,
    {plotFriedEggs(A,eggs=TRUE,rings=FALSE);
     pause("Here are the eggs...(Press Enter for next)"}),
    {plotFriedEggs(A,eggs=FALSE,rings=TRUE);
     pause("Here are the rings...(Press Enter for next)"}),
    {plotFriedEggs(A,eggs=FALSE,rings=FALSE);
     cat("Here is the pepper alone.\n")} )
```

plotTrace

Plot Trace Lines from a Data Frame, Matrix, or Vector

Description

Plot trace lines from a data frame or matrix where the first field contains x-values, and subsequent fields give y-values to be traced over x. If input is a vector, this is traced over the number of observations.

Usage

```
plotTrace(file, clr=c("blue","red","green","magenta","navy"), ...)
```

Arguments

file	data frame or matrix of x and y-values, or a vector of y-values.
clr	vector of colours. Patterns are repeated if the number of traces (y-fields) exceeded the length of clr.
...	additional arguments for plot or lines.

Details

This function is designed primarily to give greater flexibility when viewing results from the R-package BRugs. Use `plotTrace` in conjunction with `samplesHistory("*",beg=0,plot=FALSE)` rather than `samplesHistory` which calls `plotHistory`.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

Examples

```
z <- data.frame(x=1:50,y1=rnorm(50,sd=3),y2=rnorm(50,sd=1),y3=rnorm(50,sd=.25))
plotTrace(z,lwd=3)
```

presentTalk

Run a Presentation in R

Description

Start an R talk from a *talk description file* that launches a control GUI.

Usage

```
presentTalk(talk)
```

Arguments

talk talk xml file name

Details

presentTalk is a tool that facilitates lectures and workshops in R. The function allows the presenter to show code snippets alongside their execution, making use of R's graphical capabilities. When presentTalk is called, a graphical user interface (GUI) is launched that allows the user to control the flow of the talk (e.g., switching between talks or skipping to various sections of a talk).

The automatic control buttons allow the user to move forward or backward in the talk. The GO button moves forward one tag segment, the Back button moves back to the previous tag segment. The blue buttons allow movement among sections - Prev to the previous section, Restart to the start of the current section, and Next to the next section. Drop down lists are provided for both indicating the current section and slide number and as an additional interface for jumping between different sections or slide numbers.

In addition to the automatic menu items, a user can add buttons to the GUI that accomplish similar purposes.

Note

See the PBSmodelling User's Guide for more information.

Author(s)

Alex Couture-Beil

See Also

See [PBStalk-class](#) for more details on **PBSmodelling**'s talk presentation classes.

Examples

```
wd <- getwd() #save current directory
talk_dir <- system.file("examples", package = "PBSmodelling" )
setwd( talk_dir )
presentTalk( "swisstalk.xml" )

#restore working directory once talk GUI is closed
setwd( wd )
```

promptOpenFile *Deprecated: Display Dialogue: Open File*

Description

Deprecated: use [selectFile](#) instead.

Usage

```
promptOpenFile(initialfile="", filetype=list(c("*","All Files")),
               open=TRUE)
```

Arguments

initialfile	file name of the text file containing the list.
filetype	a list of character vectors indicating file types made available to users of the GUI. Each vector is of length one or two. The first element specifies either the file extension or "*" for all file types. The second element gives an optional descriptor name for the file type. The supplied filetype list appears as a set of choices in the pull-down box labelled "Files of type:".
open	logical: if TRUE display Open prompt, if FALSE display Save As prompt.

Value

The file name and path of the file selected by the user.

Note

*** This function is deprecated and will be removed in a future version. Use [selectFile](#). ***

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[selectFile](#)

promptSaveFile	<i>Deprecated: Display Dialogue: Save File</i>
----------------	--

Description

Deprecated: use [selectFile](#) instead.

Usage

```
promptSaveFile(initialfile="", filetype=list(c("*", "All Files")),
               save=TRUE)
```

Arguments

initialfile	file name of the text file containing the list.
filetype	a list of character vectors indicating file types made available to users of the GUI. Each vector is of length one or two. The first element specifies either the file extension or "*" for all file types. The second element gives an optional descriptor name for the file type. The supplied filetype list appears as a set of choices in the pull-down box labelled "Files of type:".
save	logical: if TRUE display Save As prompt, if FALSE display Open prompt.

Value

The file name and path of the file selected by the user.

Note

*** This function is deprecated and will be removed in a future version. Use [selectFile](#). ***

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[selectFile](#)

promptWriteOptions *Prompt the User to Write Changed Options*

Description

If changes have been made to PBS options, this function allows the user to choose whether to write PBS options to an external file that can be loaded later by readPBSOptions.

Usage

```
promptWriteOptions(fname="")
```

Arguments

fname name of file where options will be saved.

Details

If there are options that have been changed in the GUI but have not been committed to PBSmodelling memory in the global R environment, the user is prompted to choose whether or not to commit these options.

Then, if any PBS options have been changed, the user is prompted to choose whether to save these options to the file fname. (When a new R session is started or when a call to readPBSOptions or writePBSOptions is made, PBS options are considered to be unchanged; when an option is set, the options are considered to be changed).

If fname="", the user is prompted to save under the file name last used by a call to readPBSOptions or writePBSOptions if available. Otherwise, the default file name "PBSOptions.txt" is used.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[writePBSOptions](#), [readPBSOptions](#), [setPBSOptions](#)

Examples

```
## Not run:  
promptWriteOptions() #uses default filename PBSOptions.txt  
  
## End(Not run)
```

readList	<i>Read a List from a File in PBS Modelling Format</i>
----------	--

Description

Read in a list previously saved to a file by `writeList`. At present, only two formats are supported - R's native format used by the `dput` function or an ad hoc PBSmodelling format. The function `readList` detects the format automatically.

For information about the PBSmodelling format, see `writeList`.

Usage

```
readList(fname)
```

Arguments

`fname` file name of the text file containing the list.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[packList](#), [unpackList](#), [writeList](#)

readPBSoptions	<i>Read PBS Options from an External File</i>
----------------	---

Description

Load options that were saved using `writePBSoptions`, for use with `openFile`, `getPBSoptions` or interfaces such as `loadC`.

Usage

```
readPBSoptions(fname="PBSoptions.txt")
```

Arguments

`fname` file name or full path of file from which the options will be loaded.

Note

If an option exists in R memory but not in the saved file, the option is not cleared from memory.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[writePBSoptions](#), [getGUIoptions](#), [openFile](#), [getPBSoptions](#)

resetGraph

Reset par Values for a Plot

Description

Reset `par()` to default values to ensure that a new plot utilizes a full figure region. This function helps manage the device surface, especially after previous plotting has altered it.

Usage

```
resetGraph(reset.mf=TRUE)
```

Arguments

`reset.mf` if TRUE reset the multi-frame status; otherwise preserve `mfrow`, `mfc01`, and `mfg`

Details

This function resets `par()` to its default values. If `reset.mf=TRUE`, it also clears the graphics device with `frame()`. Otherwise, the values of `mfrow`, `mfc01`, and `mfg` are preserved, and graphics continues as usual in the current plot. Use `resetGraph` only before a high level command that would routinely advance to a new frame.

Value

invisible return of the reset value `par()`

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

`restorePar`*Get Actual Parameters from Scaled Values*

Description

Restore scaled parameters to their original units. Used in minimization by calcMin.

Usage

```
restorePar(S,pvec)
```

Arguments

S	scaled parameter vector.
pvec	a data frame comprising four columns - c("val", "min", "max", "active") and as many rows as there are model parameters. The "active" field (logical) determines whether the parameters are estimated (TRUE) or remain fixed (FALSE).

Details

Restoration algorithm: $P = P_{min} + (P_{max} - P_{min})(\sin(\frac{\pi S}{2}))^2$

Value

Parameter vector converted from scaled units to original units specified by pvec.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

See Also

[scalePar](#), [calcMin](#), [GT0](#)

Examples

```
pvec <- data.frame(val=c(1,100,10000),min=c(0,0,0),max=c(5,500,50000),
  active=c(TRUE,TRUE,TRUE))
S <- c(.5,.5,.5)
P <- restorePar(S,pvec)
print(cbind(pvec,S,P))
```

runDemos

Interactive GUI for R Demos

Description

An interactive GUI for accessing demos from any R package installed on the user's system. runDemos is a convenient alternative to R's demo function.

Usage

```
runDemos(package)
```

Arguments

package display demos from a particular package (optional).

Details

If the argument package is not specified, the function will look for demos in all packages installed on the user's system.

Note

The runDemos GUI attempts to retain the user's objects and restore the working directory. However, pre-existing objects will be overwritten if their names co-incide with names used by the various demos. Also, depending on conditions, the user may lose working directory focus. We suggest that cautious users run this demo from a project where data objects are not critical.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[runExamples](#) for examples specific to **PBSmodelling**.

runExample*Run a Single GUI Example Included with PBS Modelling*

Description

Display a GUI to demonstrate one PBS Modelling example.

The example source files can be found in the R directory `.../library/PBSmodelling/examples`.

Usage

```
runExample(ex, pkg="PBSmodelling")
```

Arguments

`ex` string specifying an example in the pkg directory examples.
`pkg` package with an examples subdirectory.

Details

If no example is specified or if the example does not exist, a GUI pops up informing you of potential choices. Note that the string choice is case-sensitive.

Some examples use external packages which must be installed to work correctly:

BRugs - LinReg, MarkRec, and CCA;
odesolve/PBSddesolve - FishRes;
PBSmapping - FishTows.

Note

The examples are copied from `.../library/PBSmodelling/examples` to R's current temporary working directory and run from there.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

See Also

[runDemos](#), [runExamples](#)

runExamples

Run GUI Examples Included with PBS Modelling

Description

Display an interactive GUI to demonstrate PBS Modelling examples.

The example source files can be found in the R directory `.../library/PBSmodelling/examples`.

Usage

```
runExamples()
```

Details

Some examples use external packages which must be installed to work correctly:

BRugs - LinReg, MarkRec, and CCA;

odesolve/PBSdresolve - FishRes;

PBSmapping - FishTows.

Note

The examples are copied from `.../library/PBSmodelling/examples` to R's current temporary working directory and run from there.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[runDemos](#), [runExample](#)

scalePar

Scale Parameters to [0,1]

Description

Scale parameters for function minimization by calcMin.

Usage

scalePar(pvec)

Arguments

pvec a data frame comprising four columns - c("val", "min", "max", "active") and as many rows as there are model parameters. The "active" field (logical) determines whether the parameters are estimated (TRUE) or remain fixed (FALSE).

Details

Scaling algorithm: $S = \frac{2}{\pi} a \sin \sqrt{\frac{P - P_{min}}{P_{max} - P_{min}}}$

Value

Parameter vector scaled between 0 and 1.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

See Also

[restorePar](#), [calcMin](#), [GT0](#)

Examples

```
pvec <- data.frame(val=c(1,100,10000),min=c(0,0,0),max=c(5,500,50000),
  active=c(TRUE,TRUE,TRUE))
S <- scalePar(pvec)
print(cbind(pvec,S))
```

selectDir

Display Dialogue: Select directory

Description

Display the default directory chooser prompt provided by the Operating System.

Usage

```
selectDir(initialdir=getwd(), mustexist=TRUE, title="",
  usewidget=NULL)
```

Arguments

initialdir	initially selected directory
mustexist	if logical value is TRUE, only a existing directory can be selected
title	title for the prompt window
usewidget	store the selected directory in the named entry widget

Value

The directory path selected by the user

Author(s)

Alex Couture-Beil

See Also

[selectFile](#)

Examples

```
## Not run:
dir(selectDir(title="select a directory to list contents of"))

#integration with widget via doAction
createWin( c( "entry foo mode=character",
  "button text=\"select dir\"
  func=doAction action=\"selectDir(usewidget='foo')\" ) , astext=TRUE )

## End(Not run)
```

selectFile

*Display Dialogue: Open or Save File***Description**

Display the default **Open** or **Save** prompt provided by the Operating System.

Usage

```
selectFile(initialfile="", initialdir=getwd(),
  filetype=list(c("*", "All Files")), mode="open", multiple=FALSE,
  title="", defaulttextension="", usewidget=NULL)
```

Arguments

initialfile	initially selected file
initialdir	initially directory the dialog opens
filetype	a list of character vectors indicating file types made available to users of the GUI. Each vector is of length one or two. The first element specifies either the file extension or "*" for all file types. The second element gives an optional descriptor name for the file type. The supplied filetype list appears as a set of choices in the pull-down box labelled "Files of type:".
mode	string: if "save" display Save As prompt, if "open" display Open prompt.
multiple	if TRUE the open prompt can select multiple files. This has no effect for the save prompt.
title	title for the prompt window
defaulttextension	default file extension if none is provided by the user
usewidget	store the selected file in the named entry widget

Value

The file name and path of the file(s) selected by the user.

Author(s)

Alex Couture-Beil

See Also[selectDir](#)**Examples**

```
## Not run:
# Open a filename, and return it line by line in a vector
scan(promptOpenFile(),what=character(),sep="\n")

# Illustrates how to set filetype.
promptOpenFile("initial_file.txt", filetype=list(c(".txt", "text files"),
        c(".r", "R files"), c("*", "All Files")))

#integration with widget via doAction
createWin( c( "entry foo mode=character",
        "button text=\"select file\"
        func=doAction action=\"selectFile(usewidget='foo')\" ) , astext=TRUE )

## End(Not run)
```

`setFileOption`*Set a PBS File Path Option Interactively*

Description

Set a PBS option by browsing for a file. This function provides an alternative to using `setPBSoptions` when setting an option that has a path to a file as its value.

Usage

```
setFileOption(option)
```

Arguments

`option` name PBS option to change

Note

If all the required arguments are missing, it is assumed that the function is being called by a GUI widget.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[setPathOption](#), [setPBSoptions](#)

Examples

```
## Not run:  
setPathOption("editor")  
  
## End(Not run)
```

setGUIoptions	<i>Set PBS Options from Widget Values</i>
---------------	---

Description

Set PBS options from corresponding values of widgets in a GUI.

Usage

```
setGUIoptions(option)
```

Arguments

`option` the name of a single option or the string "*".

Details

A GUI may have PBS options that it uses, which have corresponding widgets that are used for entering values for these options. These are declared by `declareGUIoptions`.

If the option argument is the name of an option, `setGUIoptions` transfers the value of this option from a same-named widget into PBS options global R environment database.

If the option argument is "*", then all the options that have been declared by `declareGUIoptions` will be transferred in this fashion.

To use this function in a *window description file*, the option argument must be specified as the action of the widget that calls `setGUIoptions` – `action=editor` or `action=*` for example.

Note

If all the required arguments are missing, it is assumed that the function is being called by a GUI widget.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[declareGUIOptions](#), [getGUIOptions](#), [setPBSOptions](#),

Examples

```
## Not run:  
setGUIOptions("editor")  
  
## End(Not run)
```

setPathOption	<i>Set a PBS Path Option Interactively</i>
---------------	--

Description

Set a PBS option by browsing for a directory. This function provides an alternative to using `setPBSOptions` when setting an option that has a path as its value.

Usage

```
setPathOption(option)
```

Arguments

option name PBS option to change

Note

If all the required arguments are missing, it is assumed that the function is being called by a GUI widget.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[setFileOption](#), [setPBSOptions](#)

Examples

```
## Not run:  
setPathOption("myPath")  
  
## End(Not run)
```

setPBSext	<i>Set a Command Associated with a File Name Extension</i>
-----------	--

Description

Set a command with an associated extension, for use in `openFile`. The command must specify where the target file name is inserted by indicating a "%f".

Usage

```
setPBSext(ext, cmd)
```

Arguments

ext	string specifying the extension suffix.
cmd	command string to associate with the extension.

Note

These values are not saved from one *PBS Modelling* session to the next.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[getPBSext](#), [openFile](#), [clearPBSext](#)

setPBSOptions	<i>Set A User Option</i>
---------------	--------------------------

Description

Options set by the user for use by other functions.

Usage

```
setPBSOptions(option, value, sublist=FALSE)
```

Arguments

option	name of the option to set.
value	new value to assign this option.
sublist	if value is a sublist (list component) of option, this list component can be changed individually using <code>sublist=TRUE</code> .

Note

A value `.PBSmod$.options$.optionsChanged` is set to TRUE when an option is changed, so that the user doesn't always have to be prompted to save the options file.

By default, `.PBSmod$.options$.optionsChanged` is not set or NULL.

Also, if an option is set to "" or NULL then it is removed.

`.initPBSoptions()` is now called first (options starting with a dot "." do not set `.optionsChanged`).

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[getPBSoptions](#), [writePBSoptions](#), [readPBSoptions](#)

 setwdGUI

Browse for Working Directory and Optionally Find Prefix

Description

Allows the user to browse a directory tree to set the working directory. Optionally, files with given suffixes can be located in the new directory.

Usage

```
setwdGUI()
```

Examples

```
createWin( "button text=\"Change working directory\" func=setwdGUI", astext=TRUE )
```

 setWidgetColor

Update Widget Color

Description

Update the foreground and background colors of a widget

Usage

```
setWidgetColor( name, radioValue, winName = .PBSmod$.activeWin, ... )
```

Arguments

name	the name of the widget
radioValue	if specified, modify a particular radio option, as identified by the value, rather than the complete set (identified by the common name)
winName	window from which to select the GUI widget. The window that most recently receive user input is used by default if winname is not supplied
...	any combination of "fg", "bg", "disablefg", "disablebg", "entryfg", "entrybg", "noeditfg", "noeditbg" arguments, depending on type of widget - see details

Details

The setWidgetColor function allows dynamic updating of widget colors during program execution. However, two factors determine whether dynamic color updating is possible for a particular widget: (i) the type of widget, and (ii) the nature of the Tk implementation in the underlying widget library. Thus, a given widget may not support all combinations of colour variables. The following widgets support the corresponding options:

button: fg, bg, disablefg

check: fg, bg, disablefg, entryfg, entrybg

data: entryfg, entrybg, noeditfg, noeditbg

droplist: fg, bg

entry: entryfg, entrybg, noeditfg, noeditbg

label: fg, bg

matrix: entryfg, entrybg, noeditfg, noeditbg

object: entryfg, entrybg, noeditfg, noeditbg

progressbar: fg, bg

radio: fg, bg

slide: fg, bg

spinbox: entryfg, entrybg

text: fg, bg

vector: entryfg, entrybg, noeditfg, noeditbg

These options are described in the PBSmodelling User Guide under Appendix A.

Be aware that Tk uses gray for the highlight color during a selection operation. This means that when the background colour is also gray, there is no visual clue that the value has been selected for a copy operation.

Author(s)

Alex Couture-Beil and Allen R. Kronlund

Examples

```
createWin("label \"hello world\" name=hello", astext=TRUE)
setWidgetColor( "hello", bg="lightgreen", fg="purple" )

createWin("vector names=v length=3 values=\"1 2 3\"", astext=TRUE)
setWidgetColor( "v[1]", entrybg="lightgreen", entryfg="purple" )
setWidgetColor( "v[2]", entrybg="green", entryfg="purple" )
setWidgetColor( "v[3]", entrybg="forestgreen", entryfg="purple" )
```

setWidgetState	<i>Update Widget State</i>
----------------	----------------------------

Description

Update the read-only state of a widget.

Usage

```
setWidgetState( varname, state, radiovalue, winname, warn=TRUE )
```

Arguments

varname	the name of the widget
state	"normal" or "disabled" and for some widgets "readonly" as described under Details below.
radiovalue	if specified, disable a particular radio option, as identified by the value, rather than the complete set (identified by the common name)
winname	window from which to select the GUI widget. The window that most recently receive user input is used by default if winname is not supplied.
warn	if TRUE, display a warning if readonly is converted to disabled (only applies for widgets that don't accept readonly)

Details

The setWidgetState function allows dynamic control of widget functioning during program execution. The function serves as a wrapper for the tkconfigure function available in the underlying Tk libraries used by PBS Modelling. Thus, setWidgetState is only available for those widgets that use Tk library widgets.

The state of the following PBS Modelling widgets can be set to "normal" or "disabled": button, check, data, droplist, entry, matrix, object, radio, slide, spinbox, table, text, and vector. When the state variable is set to "disabled", values displayed in the widget cannot be changed or copied except in the case of the object and table widgets which permit the values to be copied.

The data, entry, matrix, and vector widgets support a "readonly" state that allows values displayed in the widget to be copied but not changed. The displayed value can be selected using the keyboard or mouse. However, the copy and paste operations can only be accomplished via Ctrl-C and Ctrl-V, respectively, not the mouse.

Be aware that Tk uses gray for the highlight color during a selection operation. This means that when the background colour is also gray, there is no visual clue that the value has been selected for a copy operation.

Exceptions to the behavior determined by state include the object, table and text widgets. There is no "readonly" state applicable to these widgets. Nevertheless, the values displayed can be copied even when the state is "disabled".

Individual radio widgets grouped by the name variable of a radio declaration can be updated by specifying radiovalue in the call to setWidgetState.

The state of individual elements in the data, matrix, and vector widgets can be updated by indexing. For the vector and matrix widgets any element can be addressed by appending the desired index to the widget name using square brackets (e.g., "myVec[2]" or "myMatrix[2,3]"). The data widget is indexed differently than the matrix widget by adding "d" after the brackets (e.g., "myData[1,1]d"). This change in syntax is required for internal coding of PBS Modelling.

Author(s)

Alex Couture-Beil and Allen R. Kronlund

Examples

```
## Not run:
winDesc <- c('vector length=3 name=vec labels="normal disabled readonly" values="1 2 3"',
            "matrix nrow=2 ncol=2 name=mat", "button name=but_name" );
createWin(winDesc, astatic=TRUE)

setWidgetState( "vec[1]", "normal" )
setWidgetState( "vec[2]", "disabled" )
setWidgetState( "vec[3]", "readonly" )

setWidgetState( "mat", "readonly" )
setWinVal( list( mat = matrix( 1:4, 2, 2 ) ) )

#works for buttons too
setWidgetState( "but_name", "disabled" )

## End(Not run)
```

setWinAct

Add a Window Action to the Saved Action Vector

Description

Append a string value specifying an action to the first position of an action vector.

Usage

```
setWinAct(winName, action)
```

Arguments

winName	window name where action is taking place.
action	string value describing an action.

Details

When a function is called from a GUI, a string descriptor associated with the action of the function is stored internally (appended to the first position of the action vector). A user can utilize this action as a type of argument for programming purposes. The command `getWinAct()[1]` yields the latest action.

Sometimes it is useful to “fake” an action. Calling `setWinAct` allows the recording of an action, even if a button has not been pressed.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

setWinVal	<i>Update Widget Values</i>
-----------	-----------------------------

Description

Update a widget with a new value.

Usage

```
setWinVal(vars, winName)
```

Arguments

vars	a list or vector with named components.
winName	window from which to select GUI widget values. The default takes the window that has most recently received new user input.

Details

The `vars` argument expects a list or vector with named elements. Every element name corresponds to the widget name which will be updated with the supplied element value.

The vector, matrix, and data widgets can be updated in several ways. If more than one name is specified for the names argument of these widgets, each element is treated like an entry widget.

If however, a single name describes any of these three widgets, the entire widget can be updated by passing an appropriately sized object.

Alternatively, any element can be updated by appending its index in square brackets to the end of the name. The data widget is indexed differently than the matrix widget by adding "d" after the brackets. This tweak is necessary for the internal coding (bookkeeping) of *PBS Modelling*. Example: "foo[1,1]d".

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[getWinVal](#), [createWin](#)

Examples

```
## Not run:
winDesc <- c("vector length=3 name=vec",
            "matrix nrow=2 ncol=2 name=mat",
            "slideplus name=foo");
createWin(winDesc, astext=TRUE)
setWinVal(list(vec=1:3, "mat[1,1]"=123, foo.max=1.5, foo.min=0.25, foo=0.7))

## End(Not run)
```

show0

Convert Numbers into Text with Specified Decimal Places

Description

Return a character representation of a number with added zeroes out to a specified number of decimal places.

Usage

```
show0(x, n, add2int=FALSE, round2n=FALSE)
```

Arguments

x	numeric data (scalar, vector, or matrix).
n	number of decimal places to show, including zeroes.
add2int	if TRUE, add zeroes to integers after the decimal.
round2n	if TRUE, round x first to n decimal places.

Value

A scalar/vector of strings representing numbers. Useful for labelling purposes.

Note

By default, this function does not round or truncate numbers. It simply adds zeroes if n is greater than the available digits in the decimal part of a number. The user can choose to round the numbers first by setting argument `round2n = TRUE`.

Author(s)

Rowan Haigh, Pacific Biological Station, Fisheries and Oceans Canada, Nanaimo BC

See Also

[pad0](#), [GT0](#)

Examples

```
frame()

#do not show decimals on integers
addLabel(0.25,0.75,show0(15.2,4))
addLabel(0.25,0.7,show0(15.1,4))
addLabel(0.25,0.65,show0(15,4))

#show decimals on integers
addLabel(0.25,0.55,show0(15.2,4,TRUE))
addLabel(0.25,0.5,show0(15.1,4,TRUE))
addLabel(0.25,0.45,show0(15,4,TRUE))
```

showAlert

Display a Message in an Alert Window

Description

Display an alert window that contains a specified message and an OK button for dismissing the window.

Usage

```
showAlert(message, title="Alert", icon="warning")
```

Arguments

message	message to display in alert window
title	title of alert window
icon	icon to display in alert window; options are "error", "info", "question", or "warning".

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[getYes](#)

Examples

```
## Not run:
showAlert("Hello World!")

## End(Not run)
```

showArgs	<i>Display Expected Widget Arguments</i>
----------	--

Description

For each widget specified, display its arguments in order with their default values. The display list can be expanded to report each argument on a single line.

Usage

```
showArgs(widget, width=70, showargs=FALSE)
```

Arguments

widget	vector string of widget names; if not specified (default), the function displays information about all widgets in alphabetical order.
width	numeric width used by <code>strwrap</code> to wrap lines of the widget usage section.
showargs	logical; if TRUE, the display also lists each argument on single line after the widget usage section.

Value

A text stream to the R console. Invisibly returns the widget usage lines.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

showHelp	<i>Display HTML Help Pages for Packages in Browser</i>
----------	--

Description

Display the help pages for installed packages that match the supplied pattern in an HTML browser window.

Usage

```
showHelp(pattern="methods", ...)
```

Arguments

pattern	string pattern to match to package names
...	allows user to specify two additional arguments: remote - character string giving a valid URL for the R_HOME directory on a remote location; update - logical: if TRUE, attempt to update the package index to reflect the currently available packages. (Not attempted if remote is non-NULL.)

Details

The specified pattern is matched to R-packages installed on the user's system. The code uses the `utils` function `browseURL` to display the HTML Help Pages using a browser that the system associates with `html` extensions. (See help for `browseURL` for other operating systems.)

Value

A list is invisibly returned, comprising:

<code>apacks</code>	all packages installed on user's system
<code>spacks</code>	selected packages based on specified pattern
<code>URLs</code>	path and file name of HTML Help Page

Help pages are displayed in a separate browser window.

Note

The connection time for browsers (at least in Windows OS) is slow. If the HTML browser program is not already running, multiple matching pages will most likely not be displayed. However, subsequent calls to `showHelp` should show all matches.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

See Also

[viewCode](#), [showPacks](#)

showPacks

Show Packages Required But Not Installed

Description

Show the packages specified by the user and compare these to the installed packages on the user's system. Display packages not installed.

Usage

```
showPacks(packs=c("PBSmodelling","PBSmapping","PBSddesolve",
  "rgl","deSolve","akima","deldir","sp","maptools","KernSmooth"))
```

Arguments

packs string vector of package names that are compared to installed packages.

Value

Invisibly returns a list of Apacks (all packages installed on user's system), Ipacks (packages in packs that are installed), and Mpacks (packages that are missing).

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

showRes

Show Results of Expression Represented by Text

Description

Evaluate the supplied expression, reflect it on the command line, and show the results of the evaluation.

Usage

```
showRes(x, cr=TRUE, pau=TRUE)
```

Arguments

x an R expression to evaluate
 cr logical: if TRUE, introduce extra carriage returns
 pau logical: if TRUE, pause after expression reflection and execution

Value

The results of the expression are return invisibly.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

Examples

```
showRes("x=rnorm(100)",pau=FALSE)
```

showVignettes	<i>Display Vignettes for Packages</i>
---------------	---------------------------------------

Description

Create a GUI that displays all vignettes for installed packages. The user can choose to view the source file for building the vignette or the final .pdf file.

Usage

```
showVignettes(package)
```

Arguments

package character string specifying package name that exists in the user's R library

Details

If the argument package is not specified, the function will look for vignettes in all packages installed on the user's system. The user can choose to view the source file for building the vignette (usually *.Rnw or *.Snw files) or the final build from the source code (*.pdf).

showVignettes uses the **PBSmodelling** function openFile to display the .Rnw and .pdf files using programs that the system associates with these extensions. On systems that do not support file extension associations, the function setPBSext can temporarily set a command to associate with an extension.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[showHelp](#), [openFile](#), [setPBSext](#), [getPBSext](#)

sortHistory	<i>Sort an Active or Saved History</i>
-------------	--

Description

Utility to sort history. When called without any arguments, an interactive GUI is used to pick which history to sort. When called with hisname, sort this active history widget. When called with file and outfile, sort the history located in file and save to outfile.

Usage

```
sortHistory(file="", outfile=file, hisname="")
```

Arguments

file	file name of saved history to sort.
outfile	file to save sorted history to.
hisname	name of active history widget and window it is located in, given in the form WINDOW.HISTORY.

Details

After selecting a history to sort (either from given arguments, or interactive GUI) the R data editor window will be displayed. The editor will have one column named `"new"` which will have numbers 1,2,3,...,n. This represents the current ordering of the history. You may change the numbers around to define a new order. The list is sorted by reassigning the index in row *i* as index *i*.

For example, if the history had three items 1,2,3. Reordering this to 3,2,1 will reverse the order; changing the list to 1,2,1,1 will remove entry 3 and create two duplicates of entry 1.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[importHistory](#), [initHistory](#)

talk-class

Present Talk Classes

Description

The function `presentTalk` is a tool that facilitates lectures and workshops in R. It allows the presenter to show code snippets alongside their execution, making use of R's graphical capabilities.

For `presentTalk` to work, six S4 class objects are created:

- talkroot element that constitutes a talk;
- section . . .branch element that defines a section within a talk;
- textleaf element that specifies text to be printed on the R console;
- fileleaf element that specifies files to be opened by the OS;
- codeleaf element that specifies R code to be executed;
- breakleaf element that specifies where to allow a break in the talk.

The leaf elements, also termed *primitive* elements, occur in isolation and cannot contain other elements. Therefore, only two levels of nesting are supported: sections within a talk and primitives within a section.

See Appendix B in the **PBSmodelling** User's Guide for more information.

Details

This function uses a convenience function called `xmlGetAttr` (from the package **XML**) that retrieves the value of a named attribute in an XML node.

The function `presentTalk` translates the XML code into a list structure called `.presentTalk` below the global object `.PBSmod`. The GUI is represented as a list structure called `presentwin` under `.PBSmod`, as for all GUI objects in **PBSmodelling**.

Slots Available

talk

name	character	string giving the name of the talk (required)
sections	list	list of sections within the talk
files	list	list of files within the talk

section

name	character	string giving the name of the section (required)
items	list	list of the four primitive (leaf-element) S4 classes
button	logical	should GUI have a button that selects section?
col	integer	column in lower section of GUI to place button
section_id	integer	specify if section does not immediately follow a talk

text

text	character	text to display on the R console
"break"	logical	break the presentation after displaying the text specified?

file

name	character	string giving the name in the GUI for a group of files to open (required)
filename	character	individual file names associated with the group name in the GUI
"break"	logical	break the presentation after opening the group of files?
button	logical	should GUI add a button that opens this group of files?
col	integer	column in lower section of GUI to place button

code

show	logical	show the code snippet in the R console?
print	logical	print the results of running the R code?
code	character	the actual chunk of R code
"break"	character	string describing where to introduce breaks in the code segment
eval	logical	evaluate the R code?

break

.xData	NULL	allows a break in the talk for user interaction on the R console.
--------	------	---

Creating S4 Objects

Objects can be created by calls of the form:

```
new("talk", name=name)
new("section",
     name      = node$attributes["name"],
     button    = as.logical(xmlGetAttr(node, "button", FALSE)),
```

```

    col      = as.integer(xmlGetAttr(node,"col",2))
new("text",
  text      = xmlValue(node),
  "break"   = as.logical(xmlGetAttr(node,"break",TRUE))
new("file",
  name      = xmlGetAttr(node,"name",""),
  "break"   = as.logical(xmlGetAttr(node,"break",TRUE)),
  filename  = xmlValue(node),
  button    = as.logical(xmlGetAttr(node,"button",FALSE)),
  col      = as.integer(xmlGetAttr(node,"col",3))
new("code",
  show      = as.logical(xmlGetAttr(node,"show",TRUE)),
  print     = as.logical(xmlGetAttr(node,"print",TRUE)),
  code     = xmlValue(node),
  "break"   = tolower(xmlGetAttr(node,"break","print")))
new("break")

```

Author(s)

Alex Couture-Beil

See Also

[presentTalk](#) for presenting a talk in R.

[xmlGetAttr](#) for retrieving the value of a named attribute in an XML node.

[setClass](#) for creating a class definition.

[PBSoptions-class](#) for a complicated S4 class implementation.

testAlpha

Test Various Alpha Transparency Values

Description

Display how the alpha transparency for `rgb()` varies.

Usage

```
testAlpha(alpha=seq(0,1,len=25), fg="blue", bg="yellow",
          border="black", grid=FALSE, ...)
```

Arguments

alpha	numeric vector of alpha transparency values values from 0 to 1.
fg	foreground colour of the top shape that varies in transparency.
bg	background colour (remains constant) of the underlying shape.
border	border colour (which also changes in transparency) of the foreground polygon.

grid logical: if TRUE, lay a grey grid on the background colour.
 ... additional graphical arguments to send to the the plotting functions.

Value

Invisibly returns the compound RGB matrix for fg, alpha, bg, and border.

Author(s)

Jon Schnute, Pacific Biological Station, Nanaimo BC

See Also

[testCol](#), [testPch](#), [testLty](#), [testLwd](#)

 testCol

Display Colours Available Using a Set of Strings

Description

Display colours as round patches in a plot. Useful for programming purposes. Colours can be specified in any of 3 different ways:

- (i) by colour name,
- (ii) by hexadecimal colour code created by `rgb()`, or
- (iii) by calling one of the colour palettes.

Usage

```
testCol(cnam=colors()[sample(length(colors()),15)])
```

Arguments

cnam vector of colour names to display. Defaults to 15 random names from the color palette to use as patterns.

Author(s)

Rowan Haigh, Pacific Biological Station, Fisheries and Oceans Canada, Nanaimo BC

See Also

[pickCol](#), [testAlpha](#), [testPch](#), [palettes](#)

Examples

```
# mix and match patterns
testCol(c("sky", "fire", "sea", "wood"))

# display transparencies of blue
testCol(rgb(0,0,1,seq(0.05,1,0.05)))

# display colours of the rainbow
testCol(rainbow(64,end=0.75))

# display basic palette colours
testCol(1:length(palette()))

# mix colour types
testCol(c("#9e7ad3", "purple", 6))
```

testLty

Display Line Types Available

Description

Display line types available.

Usage

```
testLty(newframe=TRUE, n=1:18, ...)
```

Arguments

<code>newframe</code>	if TRUE, create a new blank frame, otherwise overlay current frame.
<code>n</code>	vector of line type numbers.
<code>...</code>	additional arguments for function lines.

Note

Quick representation of line types for reference purposes.

Author(s)

Rowan Haigh, Pacific Biological Station, Fisheries and Oceans Canada, Nanaimo BC

See Also

[testLwd](#), [testPch](#), [testCol](#)

testLwd	<i>Display Line Widths</i>
---------	----------------------------

Description

Display line widths. User can specify particular ranges for lwd. Colours can also be specified and are internally repeated as necessary.

Usage

```
testLwd(lwd=1:20, col=c("black", "blue"), newframe=TRUE)
```

Arguments

lwd	line widths to display. Ranges can be specified.
col	colours to use for lines. Patterns are repeated if <code>length(lwd) > length(col)</code> .
newframe	if TRUE, create a new blank frame, otherwise overlay current frame.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

Examples

```
testLwd(3:15, col=c("salmon", "aquamarine", "gold"))
```

testPch	<i>Display Plotting Symbols or Octal Strings</i>
---------	--

Description

Display plotting symbols or octal strings. User can specify particular ranges (increasing continuous integer) for pch.

Usage

```
testPch(pch=1:100, ncol=10, grid=TRUE, newframe=TRUE, octal=FALSE, ...)
```

Arguments

pch	symbol codes or octal string numbers.
ncol	number of columns in display (can only be 2, 5, or 10). Most sensibly this is set to 10.
grid	logical: if TRUE, grid lines are plotted for visual aid.
newframe	logical: if TRUE reset the graph, otherwise overlay on top of the current graph.
octal	logical: if TRUE, show octal strings (backslash characters) used in text statements (e.g., "30\272C" = 30°C).
...	additional arguments for functions points or text.

Author(s)

Rowan Haigh, Pacific Biological Station, Fisheries and Oceans Canada, Nanaimo BC

See Also

[testLty](#), [testLwd](#), [addLabel](#)

Examples

```
testPch(123:255)
testPch(1:25,ncol=5)
testPch(41:277,octal=TRUE)
```

testWidgets

Display Sample GUIs and their Source Code

Description

Display an interactive GUI to demonstrate the available widgets in PBS Modelling. A text window displays the *window description file* source code. The user can modify this sample code and recreate the test GUI by pressing the button below.

The *Window Description Files* can be found in the R directory
.../library/PBSmodelling/testWidgets.

Usage

```
testWidgets()
```

Details

Following are the widgets and default values supported by PBS Modelling. For detailed descriptions, see Appendix A in 'PBSModelling-UG.pdf' located in the R directory ../library/PBSmodelling/doc.

```
button text="Calculate" font="" fg="black" bg="" disablefg=NULL
      width=0 name=NULL function="" action="button" sticky=""
      padx=0 pady=0
```

```
check name mode="logical" checked=FALSE text="" font="" fg="black"
      bg="" disablefg=NULL function="" action="check" edit=TRUE
      sticky="" padx=0 pady=0
```

```
data nrow ncol names modes="numeric" rowlabels="" collabels=""
      rownames="X" colnames="Y" font="" fg="black" bg="" entryfont=""
      entryfg="black" entrybg="white" noeditfg="black" noeditbg="gray"
      values="" byrow=TRUE function="" enter=TRUE action="data"
      edit=TRUE width=6 borderwidth=0 sticky="" padx=0 pady=0
```

```
droplist name values=NULL choices=NULL labels=NULL selected=1
      add=FALSE font="" fg="black" bg="white" function="" enter=TRUE
      action="droplist" edit=TRUE mode="character" width=20
      sticky="" padx=0 pady=0
```

```
entry name value="" width=20 label=NULL font="" fg="" bg=""
      entryfont="" entryfg="black" entrybg="white" noeditfg="black"
      noeditbg="gray" edit=TRUE password=FALSE function="" enter=TRUE
      action="entry" mode="numeric" sticky="" padx=0 pady=0
```

```
grid nrow=1 ncol=1 toptitle="" sidetitle="" topfont="" sidefont=""
      topfg=NULL sidefg=NULL fg="black" topbg=NULL sidebg=NULL bg=""
      byrow=TRUE borderwidth=1 relief="flat" sticky="" padx=0 pady=0
```

```
history name="default" function="" import="" fg="black" bg=""
      entryfg="black" entrybg="white" text=NULL textsize=0 sticky=""
      padx=0 pady=0
```

```
image file=NULL varname=NULL subsample=NULL sticky="" padx=0 pady=0
```

```
include file=NULL name=NULL
```

```
label text="" name="" mode="character" font="" fg="black" bg=""
      sticky="" justify="left" anchor="center" wraplength=0 width=0
      padx=0 pady=0
```

```
matrix nrow ncol names rowlabels="" collabels="" rownames=""
      colnames="" font="" fg="black" bg="" entryfont="" entryfg="black"
      entrybg="white" noeditfg="black" noeditbg="gray" values=""
      byrow=TRUE function="" enter=TRUE action="matrix" edit=TRUE
```

```
mode="numeric" width=6 borderwidth=0 sticky="" padx=0 pady=0

menu nitems=1 label font="" fg="" bg=""

menuitem label font="" fg="" bg="" function action="menuitem"

notebook tabs name=NULL selected=1 tabpos="top" font="" fg=NULL
  bg=NULL width=0 height=0 homogeneous=FALSE arcradius=2
  tabbevelsize=0 function=NULL action="notebook" sticky="we"
  padx=0 pady=0

null bg="" padx=0 pady=0

object name rowshow=0 font="" fg="black" bg="" entryfont=""
  entryfg="black" entrybg="white" noeditfg="black" noeditbg="gray"
  vertical=FALSE collabels=TRUE rowlabels=TRUE function=""
  enter=TRUE action="data" edit=TRUE width=6 borderwidth=0
  sticky="" padx=0 pady=0

progressbar name value=0 maximum=100 style="normal" width=NULL
  height=NULL vertical=FALSE fg=NULL bg=NULL relief="sunken"
  borderwidth=2 sticky="" padx=0 pady=0

radio name value text="" font="" fg="black" bg="" function=""
  action="radio" edit=TRUE mode="numeric" selected=FALSE
  sticky="" padx=0 pady=0

slide name from=0 to=100 value=NA showvalue=FALSE
  orientation="horizontal" font="" fg="black" bg="" function=""
  action="slide" sticky="" padx=0 pady=0

slideplus name from=0 to=1 by=0.01 value=NA font="" fg="black"
  bg="" entryfont="" entryfg="black" entrybg="white" function=""
  enter=FALSE action="slideplus" sticky="" padx=0 pady=0

spinbox name from to by=1 value=NA label="" font="" fg="black"
  bg="" entryfont="" entryfg="black" entrybg="white" function=""
  enter=TRUE edit=TRUE action="droplist" width=20 sticky=""
  padx=0 pady=0

table name rowshow=0 font="" fg="black" bg="white" rowlabels=""
  collabels="" function="" action="table" edit=TRUE width=10
  sticky="" padx=0 pady=0

text name height=8 width=30 edit=FALSE scrollbar=TRUE fg="black"
  bg="white" mode="character" font="" value="" borderwidth=1
  relief="sunken" sticky="" padx=0 pady=0
```

```
vector names length=0 labels="" values="" vecnames="" font=""
  fg="black" bg="" entryfont="" entryfg="black" entrybg="white"
  noeditfg="black" noeditbg="gray" vertical=FALSE function=""
  enter=TRUE action="vector" edit=TRUE mode="numeric" width=6
  borderwidth=0 sticky="" padx=0 pady=0

window name="window" title="" vertical=TRUE bg="#D4D0C8"
  fg="#000000" onclose="" remove=FALSE
```

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[createWin](#), [showArgs](#)

unpackList

Unpack List Elements into Variables

Description

Make local or global variables (depending on the scope specified) from the named components of a list.

Usage

```
unpackList(x, scope="L")
```

Arguments

x	named list to unpack.
scope	If "L", create variables local to the parent frame that called the function. If "G", create global variables.

Value

A character vector of unpacked variable names.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[packList](#), [readList](#), [writeList](#)

Examples

```
x <- list(a=21,b=23);
unpackList(x);
print(a);
```

`updateGUI`*Update Active GUI With Local Values*

Description

Update the currently active GUI with values from R's memory at the specified location.

Usage

```
updateGUI(scope = "L")
```

Arguments

scope	either "L" for the parent frame, "G" for the global environment, or an explicit R environment
-------	---

Details

If the characteristics of the local R objects do not match those of the GUI objects, the update will fail.

Value

Invisibly returns a Boolean vector that specifies whether the objects in the local R environment match items in the active GUI.

Author(s)

Rob Kronlund, Pacific Biological Station, Nanaimo BC

See Also

[getWinVal](#), [setWinVal](#)

Examples

```
#law of free food: http://www.phdcomics.com/comics.php?f=1223
createWin( c(
  "vector names=\"foodquality hunger cost\" values=\"0.6 0.8 0.1\" width=10",
  "entry name=taste edit=F label=taste:" ), astext=TRUE )
getWinVal( scope="L" )
taste <- foodquality * hunger / cost
updateGUI()
```

vbdata *Data: Lengths-at-Age for von Bertalanffy Curve*

Description

Lengths-at-age for freshwater mussels (*Anodonta kennerlyi*).

Usage

```
data(vbdata)
```

Format

A data frame with 16 rows and 2 columns `c("age", "len")`.

Details

Data for demonstration of the von Bertalanffy model used in the `calcMin` example.

Source

Fisheries and Oceans Canada - Mittertreiner and Schnute (1985)

References

Mittertreiner, A. and Schnute, J. (1985) Simplex: a manual and software package for easy nonlinear parameter estimation and interpretation in fishery research. *Canadian Technical Report of Fisheries and Aquatic Sciences* **1384**, xi + 90 pp.

vbpars *Data: Initial Parameters for a von Bertalanffy Curve*

Description

Starting parameter values for `Linf`, `K`, and `t0` for von Bertalanffy minimization using length-at-age data (`vbdata`) for freshwater mussels (*Anodonta kennerlyi*).

Usage

```
data(vbpars)
```

Format

A matrix with 3 rows and 3 columns `c("Linf", "K", "t0")`. Each row contains the starting values, minima, and maxima, respectively, for the three parameters.

Details

Data for demonstration of the von Bertalanffy model used in the [calcMin](#) example.

References

Mittertreiner, A. and Schnute, J. (1985) Simplex: a manual and software package for easy nonlinear parameter estimation and interpretation in fishery research. *Canadian Technical Report of Fisheries and Aquatic Sciences* **1384**, xi + 90 pp.

 view

View First/Last/Random n Elements/Rows of an Object

Description

View the first or last or random n elements or rows of an object. Components of lists will be subset also.

Usage

```
view(obj, n=5, last=FALSE, random=FALSE, ...)
```

Arguments

obj	object to view.
n	first (default)/last/random n elements/rows of obj to view.
last	logical: if TRUE, last n elements/rows of obj are displayed.
random	logical: if TRUE, n random elements/rows (without replacement) of obj are displayed.
...	additional arguments (e.g., replace=T if specifying random=T).

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

`viewCode`*View Package R Code*

Description

View the R code of all functions in a specified package installed on the user's system.

Usage

```
viewCode(pkg="PBSmodelling", funs, output=4, ...)
```

Arguments

<code>pkg</code>	string name of a package installed on the user's computer.
<code>funs</code>	string vector of explicit function names from <code>pkg</code> to view.
<code>output</code>	numeric value: 1 = function names only, 2 = function names with brief description, 3 = functions and their arguments, and 4 = function R-code (default).
<code>...</code>	allows user to specify two additional arguments for <code>output=2</code> : <code>remote</code> - character string giving a valid URL for the <code>R_HOME</code> directory on a remote location; <code>update</code> - logical: if TRUE, attempt to update the package index to reflect the currently available packages. (Not attempted if <code>remote</code> is non-NULL.)

Also, if user specifies `pat=TRUE`, then `funs`, if specified, are treated like patterns.

Details

If `funs` is not specified, then all functions, including hidden (dot) functions are displayed.
If the package has a namespace, functions there are also displayed.

Value

Invisibly returns source code of all functions in the specified package. The function invokes `openFile` to display the results.

Author(s)

Rowan Haigh, Pacific Biological Station, Nanaimo BC

See Also

[showHelp](#), [view](#)

 writeList

 Write a List to a File in PBS Modelling Format

Description

Write an ASCII text representation in either "D" format or "P" format. The "D" format makes use of `dput` and `dget`, and produces an R representation of the list. The "P" format represents a simple list in an easy-to-read, ad hoc PBSmodelling format.

Usage

```
writeList(x, fname, format="D", comments="")
```

Arguments

<code>x</code>	R list object to write to an ASCII text file.
<code>fname</code>	file name of the text file containing the list.
<code>format</code>	format of the file to create: "D" or "P".
<code>comments</code>	vector of character strings to use as initial-line comments in the file.

Details

The "D" format is equivalent to using R's base functions `dput` and `dget`, which support all R objects.

The "P" format only supports named lists of vectors, matrices, arrays, and data frames. Scalars are treated like vectors. Nested lists are not supported.

The "P" format writes each named element in a list using the following conventions: (i) `\$` followed by the name of the data object to denote the start of that object's description; (ii) `\$\$` on the next line to describe the object's structure - object type, mode(s), names (if vector), rownames (if matrix or data), and colnames (if matrix or data); and (iii) subsequent lines of data (one line for vector, multiple lines for matrix or data).

Arrays with three or more dimensions have `dim` and `dimnames` arguments. `Dim` is the dimension of the data, a vector as returned by `dim(some_array)`, and `dimnames` is a vector of length `sum(dim(some_array)+1)` and is constructed as follows:

```
foreach dimension d first append the name of the dimension d then append all
labels within that dimension
```

Multiple rows of data for matrices or data frames must have equal numbers of entries (separated by whitespace).

Using "P" formatting, array data are written the same way that they are displayed in the R console: `nrow=dim()[1], ncol=dim()[2]` repeated by scrolling through successively higher dimensions, increasing the index from left to right within each dimension. The flattened table will have `dim()[2]` columns.

For complete details, see "PBSmodelling-UG.pdf" in the R directory `.../library/PBSmodelling/doc`.

Author(s)

Alex Couture-Beil, Malaspina University-College, Nanaimo BC

See Also

[packList](#), [readList](#), [unpackList](#)

Examples

```
## Not run:
test <- list(a=10,b=euro,c=view(WorldPhones),d=view(USArrests))
writeList(test,"test.txt",format="P",
comments=" Scalar, Vector, Matrix, Data Frame")
openFile("test.txt")

## End(Not run)

##Example of dimnames for Arrays
dimnames(Titanic)
writeList( list( Titanic ), format="P")
```

writePBSOptions

Write PBS Options to an External File

Description

Save options that were set using `setPBSOptions`, `setPBSext`, or interfaces such as `loadC`. These options can be reloaded using `readPBSOptions`.

Usage

```
writePBSOptions(fname="PBSOptions.txt")
```

Arguments

`fname` file name or full path of file to which the options will be saved.

Note

Options with names starting with "." will not be saved.

Author(s)

Anisa Egeli, Vancouver Island University, Nanaimo BC

See Also

[readPBSOptions](#), [setPBSOptions](#), [setPBSext](#), [promptWriteOptions](#)

Index

- *Topic **arith**
 - calcFib, 6
 - calcGM, 7
- *Topic **array**
 - genMatrix, 32
- *Topic **character**
 - convSlashes, 20
 - doAction, 25
 - evalCall, 26
 - showArgs, 90
 - showPacks, 91
 - viewCode, 107
- *Topic **classes**
 - PBSoptions-class, 58
 - talk-class, 94
- *Topic **color**
 - pickCol, 59
 - testAlpha, 96
 - testCol, 97
 - testLty, 98
 - testLwd, 99
 - testPch, 99
- *Topic **datasets**
 - CCA.qbr, 10
 - vbdata, 105
 - vbpars, 105
- *Topic **data**
 - clipVector, 17
- *Topic **device**
 - chooseWinVal, 11
 - clearRcon, 16
 - expandGraph, 27
 - getChoice, 33
 - resetGraph, 72
 - showHelp, 90
- *Topic **documentation**
 - openUG, 53
- *Topic **file**
 - findPrefix, 29
 - findProgram, 30
 - openExamples, 48
 - openFile, 49
 - openPackageFile, 51
 - openProjFiles, 52
 - packList, 54
 - promptOpenFile, 68
 - promptSaveFile, 69
 - readList, 71
 - selectDir, 77
 - selectFile, 78
 - unpackList, 103
 - writeList, 108
- *Topic **graphs**
 - plotACF, 60
 - plotDens, 64
 - plotTrace, 66
- *Topic **hplot**
 - drawBars, 26
 - plotAsp, 61
 - plotBubbles, 62
 - plotCsum, 63
 - plotFriedEggs, 65
- *Topic **interface**
 - compileC, 19
 - loadC, 46
- *Topic **iplot**
 - addArrows, 4
 - addLabel, 5
 - addLegend, 6
- *Topic **list**
 - exportHistory, 28
 - importHistory, 42
 - packList, 54
 - parseWinFile, 56
 - readList, 71
 - sortHistory, 93
 - unpackList, 103
 - writeList, 108

- *Topic **methods**
 - clearAll, 15
 - clearPBSext, 15
 - clearWinVal, 17
 - focusWin, 31
 - getOptions, 35
 - getOptionsFileName, 35
 - getOptionsPrefix, 36
 - getPBSext, 37
 - getPBSoptions, 38
 - getWinAct, 38
 - getWinFun, 39
 - getWinVal, 39
 - loadOptions, 47
 - loadOptionsGUI, 48
 - PBSoptions-class, 58
 - setPBSext, 82
 - setPBSoptions, 82
 - setWidgetColor, 83
 - setWidgetState, 85
 - setWinAct, 86
 - setWinVal, 87
 - updateGUI, 104
- *Topic **nonlinear**
 - calcMin, 8
- *Topic **optimize**
 - calcMin, 8
 - GT0, 41
 - restorePar, 73
 - scalePar, 76
- *Topic **package**
 - openUG, 53
 - PBSmodelling, 57
 - showPacks, 91
 - viewCode, 107
- *Topic **print**
 - pad0, 55
 - show0, 88
 - view, 106
- *Topic **programming**
 - compileC, 19
 - evalCall, 26
 - loadC, 46
- *Topic **utilities**
 - chooseWinVal, 11
 - cleanProj, 13
 - cleanWD, 14
 - clipVector, 17
 - closeWin, 18
 - compileDescription, 20
 - createVector, 21
 - createWin, 22
 - doAction, 25
 - findPat, 29
 - getChoice, 33
 - initHistory, 43
 - isWhat, 45
 - pause, 57
 - runDemos, 74
 - runExample, 74
 - runExamples, 75
 - showArgs, 90
 - showHelp, 90
 - showRes, 92
 - showVignettes, 93
 - testCol, 97
 - testLty, 98
 - testLwd, 99
 - testPch, 99
 - testWidgets, 100
- addArrows, 4, 5, 6
- addHistory (initHistory), 43
- addLabel, 5, 5, 6, 100
- addLegend, 5, 6
- backHistory (initHistory), 43
- break-class (talk-class), 94
- calcFib, 6
- calcGM, 7
- calcMin, 8, 9, 42, 73, 77, 105, 106
- CCA.qbr, 10
- chooseWinVal, 11, 34, 41
- cleanProj, 13
- cleanWD, 14, 16
- clearAll, 15
- clearHistory (initHistory), 43
- clearPBSext, 15, 16, 37, 50, 82
- clearRcon, 16
- clearWinVal, 16, 17, 40
- clipVector, 17
- closeWin, 18, 23
- code-class (talk-class), 94
- compileC, 19, 47
- compileDescription, 20, 23, 56
- convSlashes, 20

- createVector, 18, 21, 23
- createWin, 18, 20, 21, 22, 56, 88, 103
- declareGUIOptions, 24, 34, 81
- doAction, 25, 27, 51, 53
- drawBars, 26
- environment, 23
- evalCall, 26
- expandGraph, 27
- exporthHistory, 28, 42, 44
- file-class (talk-class), 94
- findPat, 29
- findPrefix, 29
- findProgram, 30
- findSuffix (findPrefix), 29
- firstHistory (initHistory), 43
- focusRcon (clearRcon), 16
- focusWin, 31
- forwHistory (initHistory), 43
- genMatrix, 32, 63
- getChoice, 12, 33, 41
- getGUIOptions, 24, 34, 72, 81
- getOptions, 35, 59
- getOptionsFileName, 35, 59
- getOptionsPrefix, 36, 59
- getPBSext, 16, 37, 38, 50, 82, 93
- getPBSoptions, 38, 72, 83
- getWinAct, 38
- getWinFun, 39
- getWinVal, 12, 17, 23, 34, 39, 88, 104
- getYes, 40, 89
- GT0, 9, 41, 73, 77, 89
- importHistory, 28, 42, 44, 94
- initHistory, 23, 28, 42, 43, 94
- isWhat, 45
- jumpHistory (initHistory), 43
- lastHistory (initHistory), 43
- loadC, 19, 46
- loadOptions, 36, 47, 59
- loadOptionsGUI, 48, 59
- openExamples, 48, 51, 53
- openFile, 16, 37, 49, 49, 51, 53, 54, 72, 82, 93
- openPackageFile, 49, 51, 53
- openProjFiles, 49, 51, 52
- openUG, 53
- packList, 54, 71, 103, 109
- pad0, 55, 89
- palettes, 97
- parseWinFile, 20, 23, 40, 56
- pause, 57
- PBSmodelling, 57
- PBSmodelling-package (PBSmodelling), 57
- PBSoptions-class, 35, 36, 47, 48, 96
- PBSoptions-class, 58
- PBSstalk-class, 67
- pickCol, 59, 97
- plotACF, 60
- plotAsp, 61
- plotBubbles, 32, 62, 66
- plotCsum, 63
- plotDens, 64
- plotFriedEggs, 65
- plotTrace, 66
- presentTalk, 67, 96
- print, PBSoptions-method
(PBSoptions-class), 58
- promptOpenFile, 42, 68
- promptSaveFile, 28, 69
- promptWriteOptions, 24, 34, 70, 109
- readList, 54, 71, 103, 109
- readPBSoptions, 34, 38, 70, 71, 83, 109
- resetGraph, 28, 72
- restorePar, 9, 42, 73, 77
- rmHistory (initHistory), 43
- runDemos, 74, 75, 76
- runExample, 74, 76
- runExamples, 74, 75, 75
- saveOptions, 36
- saveOptions (loadOptions), 47
- saveOptionsAs (loadOptions), 47
- saveOptionsGUI (loadOptionsGUI), 48
- scalePar, 9, 42, 66, 73, 76
- section-class (talk-class), 94
- selectDir, 77, 79
- selectFile, 68, 69, 77, 78
- setClass, 96
- setFileOption, 79, 81
- setGUIOptions, 24, 34, 80
- setOptions (getOptions), 35

setOptionsFileName
 (getOptionsFileName), 35
setOptionsPrefix (getOptionsPrefix), 36
setPathOption, 80, 81
setPBSext, 16, 37, 50, 51, 53, 82, 93, 109
setPBSoptions, 70, 80, 81, 82, 109
setwdGUI, 83
setWidgetColor, 83
setWidgetState, 85
setWinAct, 86
setWinVal, 12, 23, 34, 40, 87, 104
show, PBSoptions-method
 (PBSoptions-class), 58
show0, 88
showAlert, 41, 89
showArgs, 90, 103
showHelp, 54, 90, 93, 107
showPacks, 91, 91
showRes, 92
showVignettes, 93
sortHistory, 93
Sys.which, 31

talk-class, 94
testAlpha, 96, 97
testCol, 60, 97, 97, 98
testLty, 97, 98, 100
testLwd, 97, 98, 99, 100
testPch, 97, 98, 99
testWidgets, 100
text-class (talk-class), 94

unpackList, 54, 71, 103, 109
updateGUI, 104

vbdata, 105, 105
vbpars, 105
view, 106, 107
viewCode, 54, 91, 107

widgets (testWidgets), 100
writeList, 54, 71, 103, 108
writePBSoptions, 50, 70, 72, 83, 109

xmlGetAttr, 96