

Package ‘RColorBrewer’

February 14, 2012

Version 1.0-5

Date 2011-06-16

Title ColorBrewer palettes

Author Erich Neuwirth <erich.neuwirth@univie.ac.at>

Maintainer Erich Neuwirth <erich.neuwirth@univie.ac.at>

Depends R (>= 2.0.0)

Description The packages provides palettes for drawing nice maps shaded according to a variable.

License Apache License 2.0

Repository CRAN

Date/Publication 2011-06-17 08:34:00

R topics documented:

RColorBrewer	1
Index	5

RColorBrewer	<i>ColorBrewer palettes</i>
--------------	-----------------------------

Description

Creates nice looking color palettes especially for thematic maps

Usage

```
brewer.pal(n, name)
display.brewer.pal(n, name)
display.brewer.all(n=NULL, type="all", select=NULL, exact.n=TRUE)
brewer.pal.info
```

Arguments

<code>n</code>	Number of different colors in the palette, minimum 3, maximum depending on palette
<code>name</code>	A palette name from the lists below
<code>type</code>	One of the string "div", "qual", "seq", or "all"
<code>select</code>	A list of names of existing palettes
<code>exact.n</code>	If TRUE, only display palettes with a color number given by <code>n</code>

Details

`brewer.pal` makes the color palettes from ColorBrewer available as R palettes.

`display.brewer.pal()` displays the selected palette in a graphics window.

`display.brewer.all()` displays the a few palettes simultaneously in a graphics window.

`brewer.pal.info` returns information about the available palettes as a dataframe. `brewer.pal.info` is not a function, it is a variable. This might change in the future.

For details and an interactive palette selection tools see <http://colorbrewer.org>. It is free to use, although ColorBrewer's designers would appreciate it if you could cite the ColorBrewer project if you decide to use one of our color schemes.

There are 3 types of palettes, sequential, diverging, and qualitative.

1. Sequential palettes are suited to ordered data that progress from low to high. Lightness steps dominate the look of these schemes, with light colors for low data values to dark colors for high data values.
2. Diverging palettes put equal emphasis on mid-range critical values and extremes at both ends of the data range. The critical class or break in the middle of the legend is emphasized with light colors and low and high extremes are emphasized with dark colors that have contrasting hues.
3. Qualitative palettes do not imply magnitude differences between legend classes, and hues are used to create the primary visual differences between classes. Qualitative schemes are best suited to representing nominal or categorical data.

The sequential palettes names are

Blues BuGn BuPu GnBu Greens Greys Oranges OrRd PuBu PuBuGn PuRd Purples RdPu Reds YlGn YlGnBu YlOrBr YlOrRd

All the sequential palettes are available in variations from 3 different values up to 9 different values.

The diverging palettes are

BrBG PiYG PRGn PuOr RdBu RdGy RdYlBu RdYlGn Spectral

All the diverging palettes are available in variations from 3 different values up to 11 different values.

For qualitative palettes, the lowest number of distinct values available always is 3, but the largest number is different for different palettes. It is given together with the palette names in the following table.

Accent	8
Dark2	8
Paired	12
Pastel1	9

Pastel2	8
Set1	9
Set2	8
Set3	12

ColorBrewer is Copyright (c) 2002 Cynthia Brewer, Mark Harrower, and The Pennsylvania State University. All rights reserved.

The ColorBrewer palettes have been included in this R package with permission of the copyright holder.

For license details see the file COPYING included in this package.

Value

A palette

You will get an error when you ask for a nonexistent palette, and you will get a warning if a palette you asked for exists but not with as many different levels as you asked for.

Note

More information on ColorBrewer is available at its Website, <http://www.colorbrewer.org>.

Author(s)

Erich Neuwirth, University of Vienna, <erich.neuwirth@univie.ac.at>, with contributions by John Maindonald, Australian National University, <john.maindonald@anu.edu.au>

Examples

```
## create a sequential palette for usage and show colors
mypalette<-brewer.pal(7,"Greens")
image(1:7,1,as.matrix(1:7),col=mypalette,xlab="Greens (sequential)",
      ylab="",xaxt="n",yaxt="n",bty="n")
Sys.sleep(2)
## display a divergent palette
display.brewer.pal(7,"BrBG")
Sys.sleep(2)
## display a qualitative palette
display.brewer.pal(7,"Accent")
Sys.sleep(2)
## display a palettes simultaneously
display.brewer.all(n=10, exact.n=FALSE)
Sys.sleep(2)
display.brewer.all(n=10)
Sys.sleep(2)
display.brewer.all()
Sys.sleep(2)
display.brewer.all(type="div")
Sys.sleep(2)
display.brewer.all(type="seq")
Sys.sleep(2)
display.brewer.all(type="qual")
```

```
Sys.sleep(2)
display.brewer.all(n=5,type="div",exact.n=TRUE)
Sys.sleep(2)
brewer.pal.info
brewer.pal.info["Blues",]
brewer.pal.info["Blues",]$maxcolors
```

Index

*Topic **color**

`RColorBrewer`, [1](#)

`brewer (RColorBrewer)`, [1](#)

`ColorBrewer (RColorBrewer)`, [1](#)

`colors (RColorBrewer)`, [1](#)

`display.brewer.all (RColorBrewer)`, [1](#)

`display.brewer.pal (RColorBrewer)`, [1](#)

`RColorBrewer`, [1](#)