

Package ‘fImport’

January 2, 2012

Version 2110.79

Revision 4826

Date 2010-04-14

Title Rmetrics - Economic and Financial Data Import

Author Diethelm Wuertz and many others, see the SOURCE file

Depends R (>= 2.6.0), methods, timeDate, timeSeries

Suggests RUnit

Maintainer Rmetrics Core Team <Rmetrics-core@r-project.org>

Description Environment for teaching “Financial Engineering and Computational Finance”

NOTE SEVERAL PARTS ARE STILL PRELIMINARY AND MAY BE CHANGED IN THE FUTURE. THIS TYPICALLY INCLUDES FUNCTION AND ARGUMENT NAMES, AS WELL AS DEFAULTS FOR ARGUMENTS AND RETURN VALUES.

LazyLoad yes

LazyData yes

License GPL (>= 2)

URL <http://www.rmetrics.org>

Repository CRAN

Date/Publication 2010-04-14 10:36:23

R topics documented:

fImport-package	2
Fred	4
fWEBDATA-class	5
Oanda	6
providerListings	8
read.lines	8
read.lynx	9
read.xls	9
readDownload	10
readSplit	10
show-methods	11
Yahoo	11
YahooBriefing	14
YahooKeystats	15
Index	16

fImport-package	<i>Import Data Package</i>
-----------------	----------------------------

Description

Package of functions to download data from the internet or from other sources.

Details

Package:	fImport
Type:	Package
Version:	270.73
Date:	2008
License:	GPL Version 2 or later
Copyright:	(c) 1999-2008 Diethelm Wuertz and Rmetrics Foundation
URL:	http://www.rmetrics.org

Overview:

The package makes functions available to download financial market data from the internet. Functions are available for the following web sites:

1. Data from research.stlouisfed.org
2. Data from www.oanda.com
3. Data from chart.yahoo.com

There are two kinds of functions available, the first kind is called *Series which downloads a "timeSeries" object from a web site where the star * is a placeholder for the web site (fred,

oanda, and yahoo), and the second kind is called `*Import` which downloads an S4 object of class `"fWEBDATA"` with a `@Data` slot which keeps the `"timeSeries"` object and further slots which keep additional download information.

We recommend the first kind of functions for easy download of economic and financial time series, whereas we recommend to use the second kind of functions when additional information is required for example for the storage of the data in a data base management system.

IMPORTANT NOTE: The download from the web site www.forecasts.org has been withdrawn since the time series are no longer updated. Note, all the series offered by the "forecasts.org" web site are also available from the FRED St. Louis database.

Downloading a 'timeSeries' Object:

The following functions

1. `fredSeries`
2. `oandaSeries`
3. `yahooSeries`

allow for an easy download of economic and financial time series data as objects of class `"timeSeries"`.

Note, with version 280.73 major changes were made in the argument list of the downloading functions. We apologize for any inconveniences caused by these changes. The reason was that now all functions have the same arguments which makes their usage much easier. For details we refer to the help pages of the functions mentioned above.

Importing a 'fWEBDATA' Object:

If you like to keep additional download information, use the functions

1. `fredImport`
2. `oandaImport`
3. `yahooImport`

which return objects of class `"fWEBDATA"`.

Key Statistics:

The function `yahooKeystats` allows to download key statistics from Yahoo's web site.

Briefing:

The function `yahooBriefings` allows to download a briefing from Yahoo's web site.

Examples:

Simple examples for downloading time series objects are given in the help pages, more elaborated examples can be found in the unit testing directory.

License:

This Rmetrics package is written for educational usage teaching "Computational Finance and Financial Engineering" and licensed under GPL.

Description

Imports financial time series data from research.stlouisfed.org.

Usage

```
fredSeries(symbols, from = NULL, to = Sys.timeDate(),
           nDaysBack = 366, ...)
```

```
fredImport(query, file = "tempfile", source = NULL, frequency = "daily",
           from = NULL, to = Sys.timeDate(), nDaysBack = NULL,
           save = FALSE, sep = ";", try = TRUE)
```

Arguments

file	a character string with filename, usually having extension ".csv", where to save the downloaded data.
frequency	a character string, one of "auto", "quarterly", "monthly", or "daily", defining the frequency of the data records. Note, the import function tries autodetect the frequency of the time series to be downloaded. This may fail, in such case specify the frequency explicitly.
from	the date from when to extract the time series.
nDaysBack	the number of days back.
query	a character string, denoting the location of the data at the web site.
save	a logical value, if set to TRUE the downloaded data file will be stored under the path and file name specified by the string file. By default FALSE.
sep	a character value specifying the column separator.
source	a character string setting the URL of the source. If NULL, then the URL will be set automatically to its default value.
symbols	a character string with the symbols to be downloaded.
to	the end date of the data download, by default the current date.
try	a logical value, if set to TRUE the Internet access will be checked.
...	optional arguments to be passed.

Value

The function `fredImport` returns an S4 object of class `fWEBDATA` with the following slots:

@call	the function call.
@data	the data as downloaded formatted as a <code>data.frame</code> .

- `@param` a character vector whose elements contain the values of selected parameters of the argument list.
- `@title` a character string with the name of the download. This can be overwritten specifying a user defined input argument.
- `@description` a character string with an optional user defined description. By default just the current date when the test was applied will be returned.

The function `fredSeries` returns an S4 object of class `timeSeries` or alternatively an object specified by the function argument `returnClass`.

Note

Internet Download Functions:

IMPORTANT NOTE: If the service provider changes the data file format it may become necessary to modify and update the functions.

Author(s)

Diethelm Wuertz for the Rmetrics R-port.

Examples

```
## Not run:  
## fredImport -  
  DPRIME = fredSeries("DPRIME")  
  tail(DPRIME)  
  
## End(Not run)
```

fWEBDATA-class

Class "fWEBDATA"

Description

The class `fWEBDATA` represents a download from the internet.

Objects from the Class

Objects can be created by calls of the `import` or `series` functions.

Slots

- call:** Object of class "call": the call of the applied function.
- data:** Object of class "data.frame": the data as downloaded formatted as a data.frame.
- param:** Object of class "character": a character vector whose elements contain the values of selected parameters of the argument list.
- title:** Object of class "character": a character string with the name of the download. This can be overwritten specifying a user defined input argument.
- description:** Object of class " character": a character string with an optional user defined description. By default just the current date and user when the test was applied will be returned.

Methods

show signature(object = "fWEBDATA"): prints an object of class 'fWEBDATA'.

Examples

```
## getClass -
  getClass("fWEBDATA")
```

 Oanda

Import FX Market Data from OANDA

Description

Imports FX market data from www.oanda.com.

Usage

```
oandaSeries(symbols, from = NULL, to = Sys.timeDate(),
            nDaysBack = 366, ...)

oandaImport(query, file = "tempfile", source = NULL, frequency = "daily",
            from = NULL, to = Sys.timeDate(), nDaysBack = 366,
            save = FALSE, sep = ";", try = TRUE)
```

Arguments

- | | |
|------------------|--|
| file | a character string with filename, usually having extension ".csv", where to save the downloaded data. |
| frequency | a character string, one of "auto", "quarterly", "monthly", or "daily", defining the frequency of the data records. Note, the import function tries autodetect the frequency of the time series to be downloaded. This may fail, in such case specify the frequency explicitly. |
| from | the date from when to extract the time series. |
| nDaysBack | the number of days back. |

query	a character string, denoting the location of the data at the web site.
save	a logical value, if set to TRUE the downloaded data file will be stored under the path and file name specified by the string <code>file</code> . By default FALSE.
sep	a character value specifying the column separator.
source	a character string setting the URL of the source. If NULL, then the URL will be set automatically to its default value.
symbols	a character string with the symbols to be downloaded.
to	the end date of the data download, by default the current date.
try	a logical value, if set to TRUE the Internet access will be checked.
...	optional arguments to be passed.

Value

The function `fredImport` returns an S4 object of class `fWEBDATA` with the following slots:

@call	the function call.
@data	the data as downloaded formatted as a <code>data.frame</code> .
@param	a character vector whose elements contain the values of selected parameters of the argument list.
@title	a character string with the name of the download. This can be overwritten specifying a user defined input argument.
@description	a character string with an optional user defined description. By default just the current date when the test was applied will be returned.

The function `fredSeries` returns an S4 object of class `timeSeries` or alternatively an object specified by the function argument `returnClass`.

Note**Internet Download Functions:**

IMPORTANT NOTE: If the service provider changes the data file format it may become necessary to modify and update the functions.

Author(s)

Diethelm Wuertz for the Rmetrics R-port.

Examples

```
## Not run:
## oandaImport -
##   oandaSeries("USD/EUR")

## End(Not run)
```

providerListings	<i>Provider Listing of symbols and descriptions</i>
------------------	---

Description

CSV files with provider listings of symbols, descriptions and related information

Format

All files are in CSV Excel spreadsheet format. The delimiter is a semicolon.

read.lines	<i>Read from a text file line by line</i>
------------	---

Description

Reads from a text file line by line.

Usage

```
read.lines(con=stdin(), n=-1, ok=TRUE, warn=FALSE, encoding="unknown")
```

Arguments

con	a connection object or a character string.
n	an integer, the (maximal) number of lines to read. Negative values indicate that one should read up to the end of input on the connection.
ok	a logical, is it OK to reach the end of the connection before $n > 0$ lines are read? If not, an error will be generated.
warn	a logical, warn if a text file is missing a final EOL. The default is FALSE, note different from function readLines.
encoding	a character string, the encoding to be assumed for input strings.

Value

the downloaded text.

read.lynx	<i>Lynx Browser interface</i>
-----------	-------------------------------

Description

Uses the Lynx Browser to read a web page.

Usage

```
read.lynx(url, intern = TRUE, bin = NULL, pipe = FALSE, ...)
```

Arguments

url	a character string specifying the URL of the web page.
intern	a logical which indicates whether to make the output of the command an R object.
bin	a string with the path of your lynx binary or NULL if lynx binary is available in the operating system path.
pipe	a logical which indicates whether the result should be returned as a pipe() command.
...	optional arguments passed to lynx binary. For example <code>accept_all_cookies = TRUE</code> or <code>cookie_file = "~/lynx_cookies"</code> . For a list of options, see the lynx manual page.

Value

the downloaded text.

read.xls	<i>Read from an xls file</i>
----------	------------------------------

Description

Reads a sheet from an xls file.

Usage

```
read.xls(url, sheet=1, lines=-1, verbose=FALSE, encoding="unknown")
```

Arguments

url	a character string specifying the URL of the web page.
sheet	an integer denoting which sheet should be extracted, by default the first.
lines	a negative integer with the lines to be skipped, by default the first.
verbose	a logical decides about verbose mode, by default FALSE.
encoding	a character string with the type of encoding, by default "unknown".

Value

the downloaded text.

readDownload	<i>Download Utilities</i>
--------------	---------------------------

Description

Some helpful download utilities.

Usage

```
composeURL(..., prefix="http://")
indexGrep(pattern, x, ...)
```

Arguments

...	[composeURL] character strings from which the URL will be composed. [indexGrep] optional arguments to be passed to the function grep.
prefix	a character string specifying the prefix of the URL.
pattern	a character string containing a regular expression to be matched in the given character vector.
x	a character vector where matches are sought.

readSplit	<i>Splitting downloaded data sets</i>
-----------	---------------------------------------

Description

Some helpful data set splitting utilities.

Usage

```
charvecSplit(x, split=" ", col=1, format="%F")
dataSplit(x, split=" ", col=-1)
```

Arguments

x	character vector to be splitted.
split	the split character, by default a blank.
col	an integer value or vector, the columns to be selected.
format	the date format of the character vector, by default the ISO-8601 date format.

show-methods

WEBDATA Download Show Methods

Description

Show methods for WEBDATA downloads.

Methods

object = "ANY" Generic function.

object = "fWEBDATA" Print function for objects of class "fWEBDATA".

Examples

```
## Not run:
## print --
  IBM = yahooImport("IBM")
  print(IBM)

## End(Not run)
```

Yahoo

Import Market Data from Yahoo

Description

Imports financial time series data from chart.yahoo.com.

Usage

```
yahooSeries(symbols, from = NULL, to = Sys.timeDate(),
            nDaysBack = 366, ...)
```

```
yahooImport(query, file = "tempfile", source = NULL,
            frequency = c("daily", "weekly", "monthly"),
            from = NULL, to = Sys.timeDate(), nDaysBack = 366,
            save = FALSE, sep = ";", try = TRUE)
```

Arguments

file a character string with filename, usually having extension ".csv", where to save the downloaded data.

frequency	a character string, one of "auto", "quarterly", "monthly", or "daily", defining the frequency of the data records. Note, the import function tries autodetect the frequency of the time series to be downloaded. This may fail, in such case specify the frequency explicitly.
from	the date from when to extract the time series.
nDaysBack	the number of days back.
query	a character string, denoting the location of the data at the web site.
save	a logical value, if set to TRUE the downloaded data file will be stored under the path and file name specified by the string file. By default FALSE.
sep	a character value specifying the column separator.
source	a character string setting the URL of the source. If NULL, then the URL will be set automatically to its default value.
symbols	a character string with the symbols to be downloaded.
to	the end date of the data download, by default the current date.
try	a logical value, if set to TRUE the Internet access will be checked.
...	optional arguments to be passed.

Details

Import data from chart.yahoo.com:

The query string is given as

```
s=SYMBOL&a=DD&b=MM&c=CCYY&g=d&q=q&z=SYMBOL&x=.csv
```

where SYMBOL has to be replaced by the symbol name of the instrument, and DD, MM, and CCYY by the day, month-1 and century/year when the time series should start.

Here are some examples of symbols:

[query]	Description:
^DJI	Dow Jones 30 Industrial Averages
^NYA	New York Stock Exchange Composite
^NDX	Nasdaq 100 Index
^IXIC	Nasdaq Composite Index
^TYX	US 30Y Treasury Bond Index
IBM	BM DJIA Stock
KO	Coca-Cola DJIA Stock

The meaning of the tokens in the query string are the following:

Token	Description
s	Selected Ticker-Symbol

a	First Quote starts with Month (mm)
b	First Quote starts with Day (dd)
c	First Quote starts with Year (ccyy)
d	Last Quote ends with Month (mm)
e	Last Quote ends with Day (dd)
f	Last Quote ends with Year (ccyy)
z	Selected Ticker-Symbol

Value

The function `yahooImport` returns an S4 object of class `fWEBSITE` with the following slots:

<code>@call</code>	the function call.
<code>@data</code>	the data as downloaded formatted as a <code>data.frame</code> .
<code>@param</code>	a character vector whose elements contain the values of selected parameters of the argument list.
<code>@title</code>	a character string with the name of the download. This can be overwritten specifying a user defined input argument.
<code>@description</code>	a character string with an optional user defined description. By default just the current date when the test was applied will be returned.

The function `yahooSeries` returns an S4 object of class `timeSeries` or alternatively an object specified by the function argument `returnClass`.

The function `keystatsImport` returns a data frame with key statistics downloaded from yahoo's web site.

Note

Internet Download Functions:

IMPORTANT NOTE: If the service provider changes the data file format it may become necessary to modify and update the functions.

Author(s)

Diethelm Wuertz for the Rmetrics R-port.

Examples

```
## Not run:
## yahooImport -
  yahooSeries("IBM")

## End(Not run)
```

Description

Imports briefings from chart.yahoo.com.

Usage

```
yahooBriefing(query, file = "tempfile", source = NULL, save = FALSE,  
              try = TRUE)
```

Arguments

file	a character string with filename, usually having extension ".csv", where to save the downloaded data.
query	a character string, denoting the location of the data at the web site.
save	a logical value, if set to TRUE the downloaded data file will be stored under the path and file name specified by the string file. By default FALSE.
source	a character string setting the URL of the source. If NULL, then the URL will be set automatically to its default value.
try	a logical value, if set to TRUE the Internet access will be checked.

Value

returns a data frame with briefings downloaded from yahoo's web site.

Author(s)

Diethelm Wuertz for the Rmetrics R-port.

Examples

```
## Not run:  
## yahooBriefing -  
  yahooBriefing("IBM")  
  
## End(Not run)
```

YahooKeystats

Import Key Statistics Data from Yahoo

Description

Imports key statistics from chart.yahoo.com.

Usage

```
yahooKeystats(query, file = "tempfile", source = NULL, save = FALSE,
              try = TRUE)
```

Arguments

file	a character string with filename, usually having extension ".csv", where to save the downloaded data.
query	a character string, denoting the location of the data at the web site.
save	a logical value, if set to TRUE the downloaded data file will be stored under the path and file name specified by the string file. By default FALSE.
source	a character string setting the URL of the source. If NULL, then the URL will be set automatically to its default value.
try	a logical value, if set to TRUE the Internet access will be checked.

Value

returns a data frame with key statistics downloaded from yahoo's web site.

Note

Function yohooKeystats has been renamed from keystatsImport.

Author(s)

Diethelm Wuertz for the Rmetrics R-port.

Examples

```
## Not run:
## yahooKeystats -
  yahooKeystats("IBM")

## End(Not run)
```

Index

- *Topic **datasets**
 - providerListings, 8
- *Topic **data**
 - fImport-package, 2
 - Fred, 4
 - fWEBDATA-class, 5
 - Oanda, 6
 - show-methods, 11
 - Yahoo, 11
 - YahooBriefing, 14
 - YahooKeystats, 15
- *Topic **programming**
 - read.lines, 8
 - read.lynx, 9
 - read.xls, 9
 - readDownload, 10
 - readSplit, 10
- amexListing (providerListings), 8
- charvecSplit (readSplit), 10
- composeURL (readDownload), 10
- dataSplit (readSplit), 10
- fImport (fImport-package), 2
- fImport-package, 2
- Fred, 4
- fredImport (Fred), 4
- fredSeries (Fred), 4
- fWEBDATA-class, 5
- h15Listing (providerListings), 8
- indexGrep (readDownload), 10
- nasdaqListing (providerListings), 8
- nyseListing (providerListings), 8
- Oanda, 6
- oandaImport (Oanda), 6
- oandaListing (providerListings), 8
- oandaSeries (Oanda), 6
- providerListings, 8
- read.lines, 8
- read.lynx, 9
- read.xls, 9
- readDownload, 10
- readSplit, 10
- show, ANY-method (show-methods), 11
- show, fWEBDATA-method (show-methods), 11
- show-methods, 11
- stoxxListing (providerListings), 8
- swxListing (providerListings), 8
- Yahoo, 11
- YahooBriefing, 14
- yahooBriefing (YahooBriefing), 14
- yahooImport (Yahoo), 11
- YahooKeystats, 15
- yahooKeystats (YahooKeystats), 15
- yahooSeries (Yahoo), 11