

Package ‘psy’

January 2, 2012

Type Package

Title Various procedures used in psychometry

Version 1.0

Date 2009-12-23

Author Bruno Falissard

Maintainer Bruno Falissard <falissard_b@wanadoo.fr>

Description Kappa, ICC, Cronbach alpha, screeplot, mtmm

License GPL (>= 2)

LazyLoad yes

Repository CRAN

Date/Publication 2009-12-24 10:42:14

R topics documented:

ckappa	2
cronbach	3
ehd	4
expsy	5
fpca	6
icc	8
lkappa	9
mdspca	10
mtmm	11
psy	12
scree.plot	13
sleep	15
sphpca	16
wkappa	18
Index	20

 ckappa

Cohen's Kappa for 2 raters

Description

Computes Cohen's Kappa for agreement in the case of 2 raters. The diagnosis (the object of the rating) may have k possible values.

Usage

```
ckappa(r)
```

Arguments

```
r          n*k matrix or dataframe, n subjects and 2 raters
```

Details

The function deals with the case where the two raters have not exactly the same scope of rating (some software associate an error with this situation). Missing value are omitted.

Value

A list with :

```
$table      the 2*k table of raw data (first rater in rows, second rater in columns)
$kappa      Cohen's Kappa
```

Author(s)

Bruno Falissard

References

Cohen, J. (1960), A coefficient of agreement for nominal scales, Educational and Psychological measurements, 20, 37-46.

Examples

```
data(expsy)
ckappa(expsy[,c(12,14)])          # Cohen's kappa for binary diagnosis

library(boot)
ckappa.boot <- function(data,x) {ckappa(data[x,]')[[2]]}
res <- boot(expsy[,c(12,14)],ckappa.boot,1000)
quantile(res$t,c(0.025,0.975))    # two-sided bootstrapped confidence interval of kappa
boot.ci(res,type="bca")          # adjusted bootstrap percentile (BCa) confidence interval (better)
ckappa(expsy[,c(11,13)])          # Cohen's kappa for non binary diagnosis
```

cronbach	<i>Cronbach's coefficient alpha</i>
----------	-------------------------------------

Description

Computes the Cronbach's reliability coefficient alpha. This coefficient may be applied to a series of items destined to be aggregated in a single score. It estimates reliability in the framework of the domain sampling model.

Usage

```
cronbach(v1)
```

Arguments

v1 n*p matrix or dataframe, n subjects and p items

Details

Missing value are omitted in a "listwise" way (all items are removed even if only one of them is missing).

Value

A list with :

```
$sample.size    Number of subjects under study
$number.of.items    Number of items of the scale or questionnaire
$alpha            alpha
```

Author(s)

Bruno Falissard

References

Nunnally, J.C., Bernstein, I.H. (1994), Psychometric Theory, 3rd edition, McGraw-Hill Series in Psychology.

Examples

```
data(expsy)
cronbach(expsy[,1:10]) ## not good because item 2 is reversed (1 is high and 4 is low)
cronbach(cbind(expsy[,c(1,3:10)],-1*expsy[,2])) ## better

datafile <- cbind(expsy[,c(1,3:10)],-1*expsy[,2])
library(boot)
```

```
cronbach.boot <- function(data,x) {cronbach(data[x,])[[3]]}
res <- boot(datafile,cronbach.boot,1000)
quantile(res$t,c(0.025,0.975)) ## two-sided bootstrapped confidence interval of Cronbach's alpha
boot.ci(res,type="bca")      ## adjusted bootstrap percentile (BCa) confidence interval (better)
```

ehd

*Depressive Mood Scale***Description**

A data frame with 269 observations on the following 20 variables. Jouvent, R et al 1988 La clinique polydimensionnelle de humeur depressive. Nouvelle version echelle EHD : Polydimensional rating scale of depressive mood. Psychiatrie et Psychobiologie.

Usage

```
data(ehd)
```

Format

This data frame contains the following columns:

- e1** Observed painfull sadness
- e2** Emotional hyperexpressiveness
- e3** Emotional instability
- e4** Observed monotony
- e5** Lack spontaneous expressivity
- e6** Lack affective reactivity
- e7** Emotional incontinence
- e8** Affective hyperesthesia
- e9** Observed explosive mood
- e10** Worried gesture
- e11** Observed anhedonia
- e12** Felt sadness
- e13** Situational anhedonia
- e14** Felt affective indifference
- e15** Hypersensibility unpleasent events
- e16** Sensory anhedonia
- e17** Felt affective monotony
- e18** Felt hyperemotionalism
- e19** Felt irritability
- e20** Felt explosive mood

Source

Jouvent, R et al 1988 La clinique polydimensionnelle de humeur depressive. Nouvelle version echelle EHD : Polydimensional rating scale of depressive mood. Psychiatrie et Psychobiologie.

Examples

```
data(ehd)
str(ehd)
```

expsy

Data set related to psychometry

Description

The expsy data frame has 30 rows and 16 columns with missing data. it1-it10 correspond to the rating of 30 patients with a 10 items scale. r1, r2, r3 to the rating of item 1 by 3 different clinicians of the same 30 patients. rb1, rb2, rb3 to the binary transformation of r1, r2, r3 (1 or 2 -> 0; and 3 or 4 -> 1) .

Usage

```
data(expsy)
```

Format

This data frame contains the following columns:

it1 a numeric vector corresponding to item 1 (rated from 1:low to 4:high)
it2 a numeric vector corresponding to item 2 (rated from 1:high to 4:low)
it3 a numeric vector corresponding to item 3 (rated from 1:low to 4:high)
it4 a numeric vector corresponding to item 4 (rated from 1:low to 4:high)
it5 a numeric vector corresponding to item 5 (rated from 1:low to 4:high)
it6 a numeric vector corresponding to item 6 (rated from 1:low to 4:high)
it7 a numeric vector corresponding to item 7 (rated from 1:low to 4:high)
it8 a numeric vector corresponding to item 8 (rated from 1:low to 4:high)
it9 a numeric vector corresponding to item 9 (rated from 1:low to 4:high)
it10 a numeric vector corresponding to item 10 (rated from 1:low to 4:high)
r1 a numeric vector corresponding to item 1 rated by rater 1
rb1 binary transformation of r1
r2 a numeric vector corresponding to item 1 rated by rater 2
rb2 binary transformation of r2
r3 a numeric vector corresponding to item 1 rated by rater 3
rb3 binary transformation of r3

Source

artificial data

Examples

```
data(expsy)
expsy[1:4,]
```

fpca

Focused Principal Components Analysis

Description

Graphical representation similar to a principal components analysis but adapted to data structured with dependent/independent variables

Usage

```
fpca(formula=NULL,y=NULL, x=NULL, data, cx=0.75, pvalues="No", partial="Yes", input="data", contraction="No", sample.size)
```

Arguments

formula	"model" formula, of the form $y \sim x$
y	column number of the dependent variable
x	column numbers of the independent (explanatory) variables
data	name of datafile
cx	size of the lettering (0.75 by default, 1 for bigger letters, 0.5 for smaller)
pvalues	vector of prespecified pvalues (pvalues="No" by default) (see below)
partial	partial="Yes" by default, corresponds to the original method (see below)
input	input="Cor" for a correlation matrix (input="data" by default)
contraction	change the aspect of the diagram, contraction="Yes" is convenient for large data set (contraction="No" by default)
sample.size	to be specified if input="Cor"

Details

This representation is close to a Principal Components Analysis (PCA). Contrary to PCA, correlations between the dependent variable and the other variables are represented faithfully. The relationships between non dependent variables are interpreted like in a PCA: correlated variables are close or diametrically opposite (for negative correlations), independent variables make a right angle with the origin. The focus on the dependent variable leads formally to a partialisation of the correlations between the non dependent variables by the dependent variable (see reference). To avoid this partialisation, the option partial="No" can be used. It may be interesting to represent graphically the strength of association between the dependent variable and the other variables using p values coming from a model. A vector of pvalue may be specified in this case.

Value

A plot (q plots in fact).

Author(s)

Bruno Falissard, Bill Morpheu, Adeline Abbe

References

Falissard B, Focused Principal Components Analysis: looking at a correlation matrix with a particular interest in a given variable. *Journal of Computational and Graphical Statistics* (1999), 8(4): 906-912.

Examples

```
data(sleep)
fpca(Paradoxical.sleep~Body.weight+Brain.weight+Slow.wave.sleep+Maximum.life.span+Gestation.time+Predation+Sle
fpca(y="Paradoxical.sleep",x=c("Body.weight","Brain.weight","Slow.wave.sleep","Maximum.life.span","Gestation.t

## focused PCA of the duration of paradoxical sleep (dreams, 5th column)
## against constitutional variables in mammals (columns 2, 3, 4, 7, 8, 9, 10, 11).
## Variables inside the red cercle are significantly correlated
## to the dependent variable with p<0.05.
## Green variables are positively correlated to the dependent variable,
## yellow variables are negatively correlated.
## There are three clear clusters of independent variables.

corsleep <- as.data.frame(cor(sleep[,2:11],use="pairwise.complete.obs"))
fpca(Paradoxical.sleep~Body.weight+Brain.weight+Slow.wave.sleep+Maximum.life.span+Gestation.time+Predation+Sle
data=corsleep,input="Cor",sample.size=60)

## when missing data are numerous, the representation of a pairwise correlation
## matrix may be preferred (even if mathematical properties are not so good...)

numer <- c(2:4,7:11)
l <- length(numer)
resu <- vector(length=l)
for(i in 1:l)
{
  int <- sleep[,numer[i]]
  mod <- lm(sleep$Paradoxical.sleep~int)
  resu[i] <- summary(mod)[[4]][2,4]*sign(summary(mod)[[4]][2,1])
}
fpca(Paradoxical.sleep~Body.weight+Brain.weight+Slow.wave.sleep+Maximum.life.span+Gestation.time+Predation+Sle
data=sleep,pvalues=resu)
## A representation with p values
## When input="Cor" or pvalues="Yes" partial is turned to "No"

mod <- lm(sleep$Paradoxical.sleep~sleep$Body.weight+sleep$Brain.weight+
sleep$Slow.wave.sleep+sleep$Maximum.life.span+sleep$Gestation.time+
sleep$Predation+sleep$Sleep.exposure+sleep$Danger)
```

```

resu <- summary(mod)[[4]][2:9,4]*sign(summary(mod)[[4]][2:9,1])
fpca(Paradoxical.sleep~Body.weight+Brain.weight+Slow.wave.sleep+Maximum.life.span+Gestation.time+Predation+Sle
data=sleep,pvalues=resu)
## A representation with p values which come from a multiple linear model
## (here results are difficult to interpret)

```

icc	<i>Intraclass correlation coefficient (ICC)</i>
-----	---

Description

Computes the ICC of several series of measurements, for example in an interrater agreement study. Two types of ICC are proposed: consistency and agreement.

Usage

```
icc(data)
```

Arguments

data n*p matrix or dataframe, n subjects p raters

Details

Missing data are omitted in a listwise way. The "agreement" ICC is the ratio of the subject variance by the sum of the subject variance, the rater variance and the residual; it is generally preferred. The "consistency" version is the ratio of the subject variance by the sum of the subject variance and the residual; it may be of interest when estimating the reliability of pre/post variations in measurements.

Value

A list with :

```

$nb.subjects    number of subjects under study
$nb.raters      number of raters
$subject.variance
                 subject variance
$rater.variance
                 rater variance
$residual       residual variance
$icc.consistency
                 Intra class correlation coefficient, "consistency" version
$icc.agreement  Intra class correlation coefficient, "agreement" version

```

Author(s)

Bruno Falissard

References

Shrout, P.E., Fleiss, J.L. (1979), Intraclass correlation: uses in assessing rater reliability, Psychological Bulletin, 86, 420-428.

Examples

```
data(expsy)
icc(expsy[,c(12,14,16)])

library(boot)
icc.boot <- function(data,x) {icc(data[x,] [[7]])}
res <- boot(expsy[,c(12,14,16)],icc.boot,1000)
quantile(res$t,c(0.025,0.975)) # two-sided bootstrapped confidence interval of icc (agreement)
boot.ci(res,type="bca")      # adjusted bootstrap percentile (BCa) confidence interval (better)
```

lkappa	<i>Light's kappa for n raters</i>
--------	-----------------------------------

Description

Computes Light's Kappa for agreement in the case of n raters. The diagnosis (the object of the rating) may have k possible values (ordered or not).

Usage

```
lkappa(r, type="Cohen", weights="squared")
```

Arguments

r	m*n matrix, m subjects and n raters
type	type="Cohen" for a categorical diagnosis. If not, the diagnosis is supposed to be ordered
weights	weights="squared" for a weighted kappa with squared weights. If not, weights are computed with absolute values.

Details

Light's Kappa is equal to the mean of the $n(n-1)/2$ kappas obtained from each pair of raters. Missing values are omitted locally when considering each pair of raters. If type="Cohen" the diagnosis is considered as a categorical variable. If not, the diagnosis is considered as an ordered variable and weighted kappa's are computed. In this last situation, the type of weights that is used (squared or absolute values) is given by the variable weights.

Value

kappa (mean of the $n(n-1)/2$ kappas obtained from each pair of raters)

Author(s)

Bruno Falissard

References

Conger, A.J. (1980), Integration and generalisation of Kappas for multiple raters, Psychological Bulletin, 88, 322-328.

Examples

```
data(expsy)
lkappa(expsy[,c(11,13,15)])      # Light's kappa for non binary diagnosis
lkappa(expsy[,c(12,14,16)])      # Light's kappa for binary diagnosis
lkappa(expsy[,c(11,13,15)], type="weighted")  # Light's kappa for non binary ordered diagnosis

library(boot)
lkappa.boot <- function(data,x) {lkappa(data[x,], type="weighted")}
res <- boot(expsy[,c(11,13,15)],lkappa.boot,1000)
quantile(res$t,c(0.025,0.975))    # Bootstrapped confidence interval of Light's kappa
boot.ci(res,type="bca")           # adjusted bootstrap percentile (BCa) confidence interval (better)
```

mdspca

Graphical representation of a correlation matrix using a Principal Component Analysis

Description

Similar to many routines, the interest is in the possible representation of both variables and subjects (and by the way categorical variables) with active and supplementary points. Missing data are omitted.

Usage

```
mdspca(datafile, supvar="no", supsubj="no", namesupvar=colnames(supvar,do.NULL=FALSE), namesupsubj=colnames(supsubj,do.NULL=FALSE))
```

Arguments

datafile	name of datafile
supvar	matrix corresponding to supplementary variables (if any), supvar="no" by default
supsubj	matrix corresponding to supplementary subjects (if any), supsubj="no" by default
namesupvar	names of the points corresponding to the supplementary variables
namesupsubj	names of the points corresponding to the supplementary subjects
dimx	rank of the component displayed on the x axis (1 by default)
dimy	rank of the component displayed on the y axis (2 by default)
cx	size of the lettering (0.75 by default, 1 for bigger letters, 0.5 for smaller)

Value

A diagram (two diagrams if supplementary subjects are used)

Author(s)

Bruno Falissard

Examples

```
data(sleep)

mdspca(sleep[,c(2:5,7:11)])
## three consistent groups of variables, paradoxical sleep (in other words: dream)
## is negatively correlated with danger

mdspca(sleep[,c(2:5,7:11)],supvar=sleep[,6],namesupvar="Total.sleep",supsubj=sleep[,1],namesupsubj="",cx=0.5)
## Total.sleep is here a supplementary variable since it is deduced
## from Paradoxical.sleep and Slow.wave.sleep
## The variable Species is displayed in the subject plane,
## Rabbit and Cow have a high level of danger
```

 mtmm

Multitrait Multimethod approach of scale validation

Description

This function is destined to assess the convergent and discriminant validity of subscales of a given scale. Items belonging to the same subscale should correlate highly amongst themselves. Items belonging to different subscales should not correlate highly. This approach is simpler and more robust than confirmatory factor analysis (CFA). It can be interesting to verify (at least approximately) the proposed structure of an existing instrument in a new population. Most psychometricians will however prefer CFA.

Usage

```
mtmm(datafile,x,color=FALSE,graph=FALSE,graphItem=FALSE)
```

Arguments

datafile	name of datafile
x	a list of variable names (as many elements as there are subscales)
color	boxplot are in colour: FALSE = colourless just in grey and white (by default), TRUE = with colours
graph	For subscale i ($i=1,\dots,n$), estimates of the Pearson's correlations between total score of subscale i and the items of subscale j ($j=1,\dots,n$). If $j=i$, the item is omitted in the computation of the total score: FALSE = no boxplot, only values, TRUE = values and boxplots

graphItem graphical representation of the correlations of a given item estimated with the option "graph=TRUE" : FALSE = no graph, True = graph but suppress previous boxplots

Value

For subscale i ($i=1,\dots,n$), displays the n boxplots of the distributions of the Pearson's correlations between items of subscale i and items of subscale j ($j=1,\dots,n$). If $j=i$, the correlation of a given item with itself is omitted. Boxplot for $i=j$ (grey by default) should be above boxplots for $i\neq j$. Likewise, the correlation of an item with the global score of its subscale should be above its correlations with the global score of the other subscales.

Author(s)

Adeline Abbe

Examples

```
data(ehd)
```

```
par(mfrow=c(1,5))
mtmm(ehd,list(c("e15","e18","e19","e20"),c("e4","e5","e6","e14","e17"),c("e11","e13","e16"),
,c("e1","e10","e12"),c("e2","e3","e7","e8","e9")))
```

Boxplots of the distributions of the Pearson's correlations between total score of subscale i and the items of subscale j

```
par(mfrow=c(1,5))
mtmm(ehd,list(c("e15","e18","e19","e20"),c("e4","e5","e6","e14","e17"),c("e11","e13","e16"),
,c("e1","e10","e12"),c("e2","e3","e7","e8","e9")),graph=TRUE)
```

Only boxplots of the distributions of the Pearson's correlations between total score of subscale i and a given item j

```
par(mfrow=c(3,2))
mtmm(ehd,list(c("e15","e18","e19","e20"),c("e4","e5","e6","e14","e17"),c("e11","e13","e16"),
,c("e1","e10","e12"),c("e2","e3","e7","e8","e9")),graphItem=TRUE)
```

Description

Kappa, Intra class correlation coefficient, Cronbach alpha, Scree plot, Multitraits multimethods, Spherical representation of a correlation matrix

Details

Package: psy
 Type: Package
 Version: 1.0
 Date: 2009-12-23
 License: free
 LazyLoad: yes

Author(s)

Bruno Falissard <falissard_b@wanadoo.fr>

References

Falissard B, A spherical representation of a correlation matrix, Journal of Classification (1996), 13:2, 267-280.
 Horn, JL (1965) A Rationale and Test for the Number of Factors in Factor Analysis, Psychometrika, 30, 179-185.
 Mammals: Ecological and Constitutional Correlates, by Allison, T. and Cicchetti, D. (1976) Science, November 12, vol. 194, pp.732-734
 Jouvent, R et al 1988 La clinique polydimensionnelle de humeur depressive. Nouvelle version echelle EHD : Polydimensional rating scale of depressive mood. Psychiatrie et Psychobiologie.

Examples

```

data(sleep)
sphpca(sleep[,c(2:5,7:11)])
data(expsy)
scree.plot(expsy[,1:10],simu=20,use="P")
data(ehd)
par(mfrow=c(1,5))
mtmm(ehd,list(c("e15","e18","e19","e20"),c("e4","e5","e6","e14","e17"),c("e11","e13","e16")
,c("e1","e10","e12"),c("e2","e3","e7","e8","e9"))))
  
```

scree.plot

Screeplot of eigenvalues, simulated data are available

Description

Graphical representation of the eigenvalues of a correlation/covariance matrix. Usefull to determine the dimensional structure of a set of variables. Simulation are proposed to help the interpretation.

Usage

```
scree.plot(namefile, title = "Scree Plot", type = "R", use = "complete.obs", simu = "F")
```

Arguments

namefile	dataset
title	Title
type	type="R" to obtain the eigenvalues of the correlation matrix of dataset, type="V" for the covariance matrix, type="M" if the input data is directly the matrix, type="E" if the input data are directly the eigenvalues
use	omit missing values by default, use="P" to analyse the pairwise correlation/covariance matrix
simu	simu=p to add p screeplots of simulated random normal data (same number of patients and variables as in the original data set, same pattern of missing data if use="P")

Details

Simulations lead sometimes to underestimate the actual number of dimensions (as opposed to Kayser rule: eigen values superior to 1). Basically, simu=20 is enough.

Value

a plot

Author(s)

Bruno Falissard

References

Horn, JL (1965) A Rationale and Test for the Number of Factors in Factor Analysis, *Psychometrika*, 30, 179-185. Cattell, RB (1966) The scree test for the number of factors. *Multivariate Behavioral Research*, 1, 245-276.

Examples

```
data(expsy)
scree.plot(expsy[,1:10],simu=20,use="P") #no obvious structure with such a small sample
```

sleep

Ecological and Constitutional Data in Mammals

Description

Data from which conclusions were drawn in the article Mammals: Ecological and Constitutional Correlates, by Allison, T. and Cicchetti, D. (1976) Science, November 12, vol. 194, pp.732-734

Usage

```
data(sleep)
```

Format

This data frame contains the following columns:

Species a factor with levels

Body.weight a numeric vector, body weight in kg

Brain.weight a numeric vector, Brain weight in g

Slow.wave.sleep a numeric vector, nondreaming sleep (hrs/day)

Paradoxical.sleep a numeric vector, dreaming sleep (hrs/day)

Total.sleep a numeric vector, nondreaming + "dreaming" (hrs/day)

Maximum.life.span a numeric vector (in years)

Gestation.time a numeric vector (in days)

Predation a numeric vector, Predation index (1 min - 5 max)

Sleep.exposure a numeric vector, Sleep exposure index (1 min - 5 max)

Danger a numeric vector, Overall danger index (1 min - 5 max)

Source

<http://lib.stat.cmu.edu/datasets/sleep>

References

Mammals: Ecological and Constitutional Correlates, by Allison, T. and Cicchetti, D. (1976) Science, November 12, vol. 194, pp.732-734

Examples

```
data(sleep)
str(sleep)
```

sphpca

*Spherical Representation of a Correlation Matrix***Description**

Graphical representation of a correlation matrix, similar to principal component analysis (PCA) but the mapping is on a sphere. The information is close to a 3d PCA, the picture is however easier to interpret since the variables are in fact on a 2d map.

Usage

```
sphpca(datafile, h=0, v=0, f=0, cx=0.75, nbsphere=2, back=FALSE, input="data", method="approx", maxiter
```

Arguments

datafile	name of datafile
h	rotation of the sphere on a horizontal plane (in degrees)
v	rotation of the sphere on a vertical plane (in degrees)
f	rotation of the sphere on a frontal plane (in degrees)
cx	size of the lettering (0.75 by default, 1 for bigger letters, 0.5 for smaller)
nbsphere	two by default: front and back
back	"FALSE" by default: the back sphere is not seen through
input	"data" by default: raw data are analysed, if not "data": correlation matrix is expected
method	"approx" by default: the estimation is based on a principal component analysis approximation. If "exact" the "approx" estimation is optimized (may be computationally consuming). if "rscal" a multidimensional scaling approach is used: distances between points on the sphere are optimized so that they represent at best the original correlations. The scaling that is used leads to angles on the sphere proportional to correlation between variables
maxiter	maximum number of iterations in the optim process
output	FALSE by default: if TRUE and method="rscal" numerical results are proposed

Details

There is an isophormism between a correlation matrix and points on the unit hypersphere of R^n . It can be shown that a 3d spherical representation of a correlation matrix is statistically and cognitively interesting (see reference). The default option method="approx" is based on a principal components approximation (see reference). It is fast and gives rather good results. If method="exact" the representation is slightly improved in terms of fit (the sphere minimizes the sum of squared distances between the original variables on the hypersphere and their projections on the sphere). The option method="rscal" optimizes the representation of correlations between variables with distances between points (in a least squares sense). For convenience, the scaling of points on the sphere is chosen so that angles between points are linearly related to correlations between variables (this

is not the case on the hypersphere were $d=[2*(1-r)]^{0.5}$. For method="exact" or method="rscal" computations may be rather lengthy (and not sensible for more than 20-40 variables). The sphere may be rotated to help in visualising most of variables on a same side (front for example). By default, the back of the sphere (right plot) is not seen showing through.

Value

A plot. If method="rscal" and output=TRUE, a list with :

```
$stress.before.optim
    Stress before optimization. The stress is equal to the sum of squares of differences between distances on the 3d sphere and distances on the hypersphere.

$stress.after.optim
    Stress after optimization.

$convergence
    If 0, convergence is OK. If not, maxiter may be increased.

$correlations
    Correlation matrix of variables (Pearson).

$residuals
    Differences between observed correlations (hypersphere) and correlations estimated from points on the 3d sphere.

$mean.abs.resid
    Mean of absolute values of residuals.
```

Author(s)

Bruno Falissard

References

Falissard B, A spherical representation of a correlation matrix, *Journal of Classification* (1996), 13:2, 267-280.

Examples

```
data(sleep)
sphpca(sleep[,c(2:5,7:11)])
## spherical representation of ecological and constitutional correlates in mammals

sphpca(sleep[,c(2:5,7:11)],method="rscal",output=TRUE)
## idem, but optimizes the representation of correlations between variables with distances between points

corsleep <- as.data.frame(cor(sleep[,c(2:5,7:11)],use="pairwise.complete.obs"))
sphpca(corsleep,input="Cor")
sphpca(corsleep,method="rscal",input="Cor")
## when missing data are numerous, the representation of a pairwise correlation
## matrix may be preferred (even if mathematical properties are not so good...)

sphpca(corsleep,method="rscal",input="Cor",h=180,f=180,nbsphere=1,back=TRUE)
## other option of presentation

##
# library(polycor)
```

```

# sleep$Predation <- as.ordered(sleep$Predation)
# sleep$Sleep.exposure <- as.ordered(sleep$Sleep.exposure)
# sleep$Danger <- as.ordered(sleep$Danger)
# corsleeph <- as.data.frame(hetcor(sleep[,c(2:5,7:11)]))$correlations)
# sphpca(corsleeph,input="Cor",f=180)
# sphpca(corsleeph,method="rscal",input="Cor",f=180)
## --> Correlations between discrete variables may appear shoking to some statisticians (?)
## --> Representation of polychoric/polyserial correlations could be prefered in this situation

```

 wkappa

weighted Kappa for 2 raters

Description

Computes a weighted Kappa for agreement in the case of 2 raters. The diagnosis (the object of the rating) may have k possible ordered values.

Usage

```
wkappa(r,weights="squared")
```

Arguments

r	n*2 matrix or dataframe, n subjects and 2 raters
weights	weights="squared" to obtain squared weights. If not, absolute weights are computed (see details)

Details

The diagnoses are ordered as follow: numbers < letters, letters and numbers ordered naturally. For weights="squared", weights are related to squared differences between rows and columns indices (in this situation wkappa is close to an icc). For weights!="squared", weights are related to absolute values of differences between rows and columns indices. The function deals with the case where the two raters have not exactly the same scope of rating (some software associate an error with this situation). Missing value are omitted.

Value

A list with :

\$table	the 2*k table of raw data (first rater in rows, second rater in columns)
\$weights	"squared" or "absolute"
\$kappa	Weighted Kappa

Author(s)

Bruno Falissard

References

Cohen, J. Weighted kappa: nominal scale agreement with provision for scaled disagreement or partial credit. *Psychological Bulletin* 70 (1968): 213-220.

Examples

```
data(expsy)
wkappa(expsy[,c(11,13)])      # weighted kappa (squared weights)

library(boot)
wkappa.boot <- function(data,x) {wkappa(data[x,])[[3]]}
res <- boot(expsy[,c(11,13)],wkappa.boot,1000)
quantile(res$t,c(0.025,0.975)) # two-sided bootstrapped confidence interval of weighted kappa
boot.ci(res,type="bca")      # adjusted bootstrap percentile (BCa) confidence interval (better)
```

Index

*Topic **datasets**

ehd, [4](#)
expsy, [5](#)
sleep, [15](#)

*Topic **multivariate**

fpca, [6](#)
mdspca, [10](#)
scree.plot, [13](#)
sphpca, [16](#)

*Topic **package**

psy, [12](#)

*Topic **univar**

ckappa, [2](#)
cronbach, [3](#)
icc, [8](#)
lkappa, [9](#)
wkappa, [18](#)

ckappa, [2](#)
cronbach, [3](#)

ehd, [4](#)
expsy, [5](#)

fpca, [6](#)

icc, [8](#)

lkappa, [9](#)

mdspca, [10](#)
mtmm, [11](#)

psy, [12](#)

scree.plot, [13](#)
sleep, [15](#)
sphpca, [16](#)

wkappa, [18](#)